

DATE: 9 September 2025
DESIGNER: DFL - UK
PROJECT No: 4074
PROJECT NAME: FOLDERS GROVE PHASE 2



Location: Folders Grove Phase 2
Environmental Zone: E2
Design Class: P5
Eav: 3.00 - 4.50 Lux
Emin: 0.60 Lux
Lighting classes as per BS5489-1:2020, the lighting levels for which
are taken from EN 13201-2:2015

4074-DFL-HLG-XX-CA-EO-13001-S3-P02

PREPARED BY: Alex Elliott
Principal Engineer
+44 (0)1962 855080
17-18 City Business Centre,
Winchester
Hants,
SO23 7TA
e-mail: alex@dfi-uk.com
website: www.dfi-uk.com

Layout Report

General Data

Dimensions in Metres Angles in Degrees

Calculation Grids

ID	Grid Name	X	Y	X' Length	Y' Length	X' Spacing	Y' Spacing
1	Grid 1 - P5	591.56	-56.10	50.52	38.22	1.49	1.47
2	Grid 2 - P5	641.49	-55.12	77.21	40.68	1.48	1.45
3	Grid 3 - P5	648.40	-129.76	29.92	79.74	1.50	1.48
4	Grid 4 - P5	704.42	-132.09	18.21	78.52	1.40	1.48
5	Grid 5 - P5	670.91	-136.64	38.17	15.62	1.47	1.42
6	Grid 6 - P5	641.11	-14.44	77.60	30.89	1.49	1.47
7	Grid 7 - P5	620.19	15.07	38.47	56.31	1.48	1.48

Luminaires

Luminaire B Data

Supplier	Urbis Schreder
Type	ALBANY GEN2 MIDI 5305 [Deep shape PC], [Lum. shape-related, P
Lamp(s)	20 LH351C@200mA WW 727 230V 01-37-043
LampFlux(klm)/Colour	2.04 WW 2700K/70
File Name	13.2W 548552 [Deep shape PC], [Lum. shape-related, Plastic, White] BL 230V EF .ldt
Maintenance Factor	0.75
Lum. Int. Class	G1
No. in Project	19

Luminaire C Data

Supplier	Urbis Schreder
Type	ALBANY GEN2 MIDI 5366 [Deep shape PC], [Lum. shape-related, P
Lamp(s)	20 LH351C@200mA WW 727 230V 01-37-043
LampFlux(klm)/Colour	2.04 WW 2700K/70
File Name	13.2W 548672 [Deep shape PC], [Lum. shape-related, Plastic, White] BL 230V EF .ldt
Maintenance Factor	0.75
Lum. Int. Class	G3
No. in Project	1

Layout


ID	Type	X	Y	Height	Angle	Tilt	Cant	Out-reach	Target X	Target Y	Target Z
1	B	710.17	-77.76	6.00	7.00	0.00	0.00	0.50			
2	B	635.36	-34.69	6.00	110.00	0.00	0.00	0.50			
3	B	655.69	-36.59	6.00	204.00	0.00	0.00	0.50			
4	B	670.95	-37.45	6.00	291.00	0.00	0.00	0.50			
5	B	698.57	-33.21	6.00	273.00	0.00	0.00	0.50			
6	B	706.98	-48.29	6.00	0.00	0.00	0.00	0.50			
7	B	710.26	-115.84	6.00	358.00	0.00	0.00	0.50			
8	B	690.84	-123.88	6.00	264.00	0.00	0.00	0.50			
9	B	672.88	-108.68	6.00	192.00	0.00	0.00	0.50			
10	B	666.37	-83.03	6.00	197.00	0.00	0.00	0.50			
12	B	658.42	-60.10	6.00	194.00	0.00	0.00	0.50			
13	B	710.60	-24.34	6.00	0.00	0.00	0.00	0.50			
14	B	660.97	-2.73	6.00	169.00	0.00	0.00	0.50			
15	B	664.88	16.24	6.00	270.00	0.00	0.00	0.50			

Layout Continued

ID	Type	X	Y	Height	Angle	Tilt	Cant	Out-reach	Target X	Target Y	Target Z
16	B	699.31	16.05	6.00	268.00	0.00	0.00	0.50			
17	B	711.08	-0.31	6.00	0.00	0.00	0.00	0.50			
18	B	648.64	30.85	6.00	191.00	0.00	0.00	0.50			
19	C	631.91	66.90	6.00	268.00	0.00	0.00	0.50			
20	B	639.47	50.13	6.00	353.00	0.00	0.00	0.50			
21	B	607.18	-36.66	6.00	248.00	0.00	0.00	0.50			

Horizontal Illuminance (lux)

Grid 1 - P5




Results

Eav	3.18
Emin	0.66
Emax	7.65
Emin/Emax	0.09
Emin/Eav	0.21

Horizontal Illuminance (lux)

Grid 2 - P5




Results

Eav	3.90
Emin	0.66
Emax	7.89
Emin/Emax	0.08
Emin/Eav	0.17

Horizontal Illuminance (lux)

Grid 3 - P5




Results

Eav	3.89
Emin	0.92
Emax	7.91
Emin/Emax	0.12
Emin/Eav	0.24

Horizontal Illuminance (lux)

Grid 4 - P5




Results

Eav	3.11
Emin	1.06
Emax	7.64
Emin/Emax	0.14
Emin/Eav	0.34

Horizontal Illuminance (lux)

Grid 5 - P5




Results

Eav	3.32
Emin	1.13
Emax	7.42
Emin/Emax	0.15
Emin/Eav	0.34

Horizontal Illuminance (lux)

Grid 6 - P5




Results

Eav	3.66
Emin	0.95
Emax	8.24
Emin/Emax	0.11
Emin/Eav	0.26

Horizontal Illuminance (lux)

Grid 7 - P5



Results

Eav	3.77
Emin	0.60
Emax	8.17
Emin/Emax	0.07
Emin/Eav	0.16