



- ## NOTES

This drawing is Copyright and shall not be produced nor used for any other purpose without the written permission of the Landscape Architects.

Do not scale from this drawing.

The Contractor is responsible for checking all dimensions on site and report any discrepancies, errors or omissions to the Landscape Architects immediately.

The Contractor shall ensure that all goods, materials and workmanship conform with current British Agreement Certificates, British Standards and Building Regulations, and ensure that all works are executed in full compliance with all current Codes of Practice and Regulations in respect of Health & Safety.

Rev	Date	By	Description	Ckd
A	29.05.24	MS	Note added	JP

Note: For Engineers Structural Drawings Refer to Dwg's A9307- VP - 002



1. Top rail: 50/10mm flat-rolled top rail
2. Fill bars: 15mm x 40mm solid infill bars at 350mm centres
3. Handrail: 316 stainless steel 45mm Ø
4. Foundation: 600mm deep, 300 x 300 square or 300 dia post hole ST4 concrete 150mm depth min from the surface (to engineers detail) 50mm Ø hole cored into paving and 'caulked' with lead.

All metalwork powdercoated corten effect

Note:

Fabricator to prepare drawings for
CA/Landscape Architect's comment and
approval.

All fixings to be
tamper proof.

All welds to be deburred and imperfections removed prior to galvanisation and factory painting.

Top rail and fill bars to be galvanised and polyester powder coated