




CONTINUATION - REFER TO SHEET 11

40mph (DIAG 670.4) north bound and 30mph (DIAG 670.3) and subplate with yellow backing board south bound lit signs on wide base post



13

5

14

13

14

13

14

13

14

13

14

13

14

13

14

13

14

13

14

13

14

13

14

13

14

13

14

13

14

13

14

13

14

13

14

13

14

13

14

13

14

13

14

13

14

13

14

13

14

13

14

13

14

13

14

13

14

13

14

13

14

13

14

13

14

13

14

13

14

13

14

13

14

13

14

13

14

13

14

13

14


13

14

CONTINUATION - REFER TO SHEET 9


Diagram: 1009A (1)	Diagram: 1004 (2)	Diagram: 1003A (3)
Width: 100 Colour: WHITE	Width: 100 Colour: WHITE	Width: 200 Colour: WHITE
Type: JUNCTION EDGE LINE	Type: 4/2 WARNING LINE	Type: GIVE WAY LINE
Mark: 600 Gap: 300	Mark: 4000 Gap: 2000	Mark: 600 Gap: 300
Studs: -	Studs: -	Studs: -
Colour: - Centres: -	Colour: - Centres: -	Colour: - Centres: -
Diagram: 1025.1 (4)	Diagram: 1025.1 (4)	Diagram: 1025.1 (4)
Width: 100 Colour: YELLOW	Width: - Colour: YELLOW	Width: 200 Colour: YELLOW
Type: BUS STOP BOUNDARY	Type: BUS STOP WORDING	Type: BUS STOP EDGE LINE
Mark: 1000 Gap: 1000	Mark: 1600 Gap: 1000	Mark: CONTIN Gap: -
Studs: -	Studs: -	Studs: -
Colour: - Centres: -	Colour: - Centres: -	Colour: - Centres: -
Diagram: 1040 (5)	Diagram: 1037.1 (6)	Diagram: 1039 (8)
Width: 150 Colour: WHITE	Height: 4000 Colour: WHITE	Height: 8 Colour: WHITE
Type: CENTRE HATCHING HATCHING	Type: TURN RIGHT ARROW	Type: BIFURCATION ARROW
Mark: 4000 Gap: 2000	Mark: - Gap: -	Mark: - Gap: -
Studs: -	Studs: -	Studs: -
Colour: - Centres: -	Colour: - Centres: -	Colour: - Centres: -
Diagram: 1018.1 (9)	Diagram: 1020.1 (9)	Diagram: 1010 (10)
Width: 100 Colour: YELLOW	Width: 100 Colour: YELLOW	Width: 100 Colour: WHITE
Type: DOUBLE YELLOW LINE	Type: DOUBLE YELLOW MARKERS	Type: PARKING BAY
Mark: CONTINU Gap: -	Mark: - Gap: 3000	Mark: 1000 Gap: 100
Studs: -	Studs: -	Studs: -
Colour: - Centres: -	Colour: - Centres: -	Colour: - Centres: -
Diagram: 1049.1 (11)	Diagram: 1024 (12)	Diagram: 1012.1 (13)
Width: 150 Colour: WHITE	Height: 1600 Colour: WHITE	Width: 100 Colour: WHITE
Type: CYCLE SEGREGATION LINE	Type: SLOW MARKING	Type: EDGE OF CARRIAGEWAY
Mark: CONTINU Gap: -	Mark: - Gap: -	Mark: - Gap: -
Studs: -	Studs: -	Studs: -
Colour: - Centres: -	Colour: - Centres: -	Colour: - Centres: -
Diagram: 1065 (14)	Diagram: 1065 (14)	Diagram: 1057 (15)
Width: 4300 Colour: WHITE	Height: 160 Colour: WHITE	Height: 1215 Colour: WHITE
Type: SPEED LIMIT ROUNDEL	Type: SPEED LIMIT MARKING	Type: CYCLE SYMBOL
Mark: CONTINU Gap: -	Mark: CONTINU Gap: -	Mark: 750 Gap: -
Studs: -	Studs: -	Studs: -
Colour: - Centres: -	Colour: - Centres: -	Colour: - Centres: -
Diagram: 1059 (15)		
Height: 1000 Colour: WHITE		
Type: CYCLE SYMBOL ARROW		
Mark: 250 Gap: -		
Studs: -		
Colour: - Centres: -		

Brook Mead





Priority over oncoming vehicles

Give way to oncoming vehicles to DIAG. 811 and 811-1 signs on new post



Give way to oncoming vehicles

Give way to oncoming vehicles to DIAG. 615 and 615-1 lit signs on wide base post



- This drawing shall be read in conjunction with all related documentation and standard details.
- The works shall be carried out in accordance with the DOT MCHV, DMRB and the local requirements of West Sussex County Council.
- Conflicting information shown on the engineer's drawings or discrepancies between the information given by the engineer and that provided by others must be referred to the engineer before the works commence.
- The Contractor shall use setting out coordinates and dimensions provided which take preference over any less accurate scaled dimensions.
- Temporary works design associated with signage shall be the responsibility of the Contractor and subject to the approval of the engineer and Highway Authority.
- Calculations and drawings of all Contractor designed items shall be submitted to the engineer for comments / approvals not less than 10 working days prior to construction. Any comments made by the engineer do not absolve the Contractor of their design responsibilities.
- All works and programming shall be agreed in advance with the overseeing organisation and the client.
- The Contractor shall maintain free and open access to the public highway and adjacent lands and properties at all time unless otherwise agreed in writing with the interested parties.
- All signs and road markings shall comply with the requirements of the Traffic Signs Manual, Traffic Sign Regulations and General Directions and those of the Adopting Authority.
- Wherever practicable signs shall be erected / mounted on other street furniture (eg lamp columns) in order to minimise clutter, as indicated on the layout and signage schedule.
- Prior to the excavation and pouring of associated foundations, the Contractor shall agree the final location of all signs and street furniture with the adopting authority.
- Road markings shall achieve a minimum SPV unless otherwise stated / agreed in writing with the adopting authority.
- The Contractor shall be responsible for liaising with the appropriate power supplier for connections previously arranged by the Client or Clients consultant to the street lighting, traffic signs & bollards and other electrical units.

- Tactile Parking
- Existing Lighting Column
- Lighting Column
- Mini-Ensign bollard and shared footway and cycleway sign, refer to ACM-CS-ZZ-DR-HW-00-0030 for details.

FOR APPROVAL

REV	DATE	DESCRIPTION
P01	12/03/2025	FOR PLANNING SUBMISSION
P04	20/12/2024	FOR PLANNING SUBMISSION
P03	15/01/2024	FOR APPROVAL
P02	12/12/2023	UPDATE FOLLOWING INTERNAL COORDINATION
P01	10/10/2023	FIRST ISSUE
REV	DATE	DESCRIPTION

