


Technical Specification

Control Point	Head (m)	Flow (l/s)
Primary Design	1.350	0.825
Flush-Flo™	0.174	0.545
Kick-Flo®	0.351	0.457
Mean Flow		0.612



hydro-int.com/patents



Head (m)	Flow (l/s)
0.000	0.000
0.047	0.365
0.093	0.513
0.140	0.541
0.186	0.545
0.233	0.539
0.279	0.524
0.326	0.491
0.372	0.469
0.419	0.493
0.466	0.516
0.512	0.537
0.559	0.558
0.605	0.577
0.652	0.596
0.698	0.615
0.745	0.632
0.791	0.649
0.838	0.665
0.884	0.681
0.931	0.697
0.978	0.712
1.024	0.727
1.071	0.741
1.117	0.755
1.164	0.769
1.210	0.783
1.257	0.796
1.303	0.809
1.350	0.821

DESIGN ADVICE



The head/flow characteristics of this SHE-0039-8250-1350-8250 Hydro-Brake® Optimum Flow Control are unique. Dynamic hydraulic modelling evaluates the full head/flow characteristic curve.

The use of any other flow control will invalidate any design based on this data and could constitute a flood risk.

Hydro
International
A CRH COMPANY

DATE	29/04/2026 10:51
Site	Little Winton
DESIGNER	Paul Tittle
Ref	15084 - S7FC (for Tank C) / 24_21_2311

SHE-0039-8250-1350-8250
Hydro-Brake® Optimum