

HYDRO-BRAKE® FLOW CONTROL MAINTENANCE AND SAFETY DATA SHEET

MAINTENANCE

Normally, little maintenance is required as there are no moving parts within the Hydro-Brake® Flow Control. Experience has shown that if blockages occur they do so at the intake, and the cause on such occasions has been due to a lack of attention to engineering detail such as approach velocities being too low, inadequate benching, or the use of units below the minimum recommended size. Hydro-Brake® Flow Controls are fitted with a pivoting by-pass door, which allows the manhole chamber to be drained down should blockages occur. The smaller type conical units, below the minimum recommended size, are also available with rodding facilities or vortex suppressor pipes as optional extras.

Following installation of the Hydro-Brake® Flow Control it is vitally important that any extraneous material ie. building materials are removed from the unit and the chamber. After the system is made live, and assuming that the chamber design is satisfactory, it is recommended that each unit be inspected monthly for three months and thereafter at six monthly intervals with hose down if required. If problems are experienced please do not hesitate to contact the company so that an investigation may be made.

Hydro-Brake® Flow Controls are typically manufactured from grade 304 Stainless Steel which has an estimated life span in excess of the design life of drainage systems.

COSHH

Hydro-Brake® Flow Controls are manufactured from Stainless Steel, which is not regarded as hazardous to health and exhibits no chemical hazard when used under normal circumstances for the stated applications.

MANUAL HANDLING

The handling of Hydro-Brake® Flow Controls should be in accordance with current legislation and regulations:

- The Health and Safety at Work Act 1974.
- The Management of Health and Safety at Work Regulations 1999.
- The Manual Handling Operations Regulations 1992.

All published and printed by the Health and Safety Executive.

HRD-FM04/16 G/0506

turning water around ...

Hydro International (UK) Ltd

Stormwater Division • Shearwater House • Clevedon Hall Estate • Victoria Road • Clevedon • BS21 7RD

Tel: 01275 878371 • Fax: 01275 874979 • www.hydro-international.biz

Registered in England No. 1474012 Registered Office: as above

A subsidiary of Hydro International plc



Certificate No. 961366



Join the Campaign
@ www.savetherain.info