

PRODUCT NAME 5MXM-A8

Dimensions	Unit		Height	mm
			Width	mm
			Depth	mm
Weight	Unit			kg
Compressor	Type			
Operation range	Cooling	Ambient	Min.	°CDB
			Max.	°CDB
Sound pressure level	Cooling		Nom.	dBA
	Heating		Nom.	dBA
Refrigerant	Type			
	Charge			kg
	Charge			tCO2Eq
	GWP			
Piping connections	Piping length	OU - IU	Max.	m
	Additional refrigerant charge			kg/m
	Level difference	IU - OU	Max.	m
		IU - IU	Max.	m
	Total piping length	System	Actual	m
Standard Accessories	Installation manual			
	Drain cap			
	Drain plug			
	Reducer assembly			
	Screw bag			
Energy Efficiency Range				
Power supply	Phase			
	Frequency			Hz
	Voltage			V
Notes				

5MXM90A2V1B8

734

974

408

68

Hermetically sealed swing compressor

-10

50

52

52

R-32

2.40

1.62

675

25 (1)

0.02 (for piping length exceeding 30m)

15

7.5

75

1

3

1

1

1

A+++ ~ D

1~

50

220-240

(1) - For one room

(2) - For combination with CVXM-A, FVXM-A - maximum piping length is 30m.

(3) - See separate drawing for operation range

(4) - See separate drawing for electrical data

(5) - Contains fluorinated greenhouse gases