



Tree Protection Area
KEEP OUT
Do **not** move this fence

Foundations within RPAs

Where piling is to be installed near to trees, the smallest practical pile diameter should be used, as this reduces the possibility of striking

— Supervised Excavation


Excavations within the RPAs will be undertaken by hand under direct on-site arboricultural supervision to a minimum of 600mm deep (to b

'No Dig' Surfacing

N8: The use of a multi-dimensional confinement system will affect the finished level of the hard surfacing by raising the levels and needs to

Arboricultural Supervision

Arboricultural Method Statement

Project:

Client: _____

Drawing:

Based on: 2025-02-10 10:23:10

Drawing No:	Rev:
44725060 TDR02	00

Date:	Scale:	Drawn:
Apr 2026	1:150	EC

Key:

RPA&		Category 'D' issue		Category 'B' group	
------	---	--------------------	---	--------------------	---

Category 'C' trees:		Category 'C' groups:		Trees to be removed:	109
---------------------	---	----------------------	---	----------------------	-----

all dimensions should be checked on site. No dimensions are to be scaled from this drawing.
Please notify us of any discrepancies found. Artech Consulting Ltd. cannot be held responsible for inaccuracies.

This drawing was produced in colour – a monochrome copy should not be used upon.