

Sustainability & Energy Statement

Land North of Burleigh Lane, Crawley Down

Prepared by Ivan Ball

Bluesky Unlimited
39 Marsh Baldon
Oxfordshire
OX44 9LP

ivan@blueskyunlimited.co.uk

27th May 2025



Table of Contents

Executive Summary	3
1.0 Introduction	5
2.0 Planning policies	6
3.0 Assessment methodology	8
4.0 Proposal	11
5.0 Energy Efficiency	12
5.1 Demand Reduction (Be Lean and Be Clean)	12
• Passive design measures	
• Active design measures	
5.2 Low-Carbon and Renewable Technologies (Be Green)	15
5.3 Establishing Carbon Dioxide Emissions	18
• SAP calculations	
5.4 Summary of Calculations and Proposals for Low-carbon & Renewable Technologies	20
6.0 Climate Change Adaption and Water Resources	21
• Sustainable drainage systems (SuDs)	
• Water efficiency measures	
7.0 Materials and Waste	23

Appendix 1: Summary SAP Reports for the Modelled Units

Executive Summary

This Sustainability and Energy Statement has been prepared in support of a detailed planning application for 48 dwellings (including affordable homes) on land north of Burleigh Lane, Crawley Down, West Sussex.

The Statement includes an energy demand assessment showing which selected energy efficiency, low-carbon and renewable energy measures have been considered and those, which could be incorporated into the development.

SAP calculations have been prepared for representative units, the results from which have been aggregated across similar unit types to provide an accurate assessment of the total site emissions.

The calculations have allowed the testing of different construction specifications and technologies and the Statement demonstrates how the buildings will exceed the requirements of the Building Regulations Part L (2021) and the objectives of the planning policy.

The calculations have been based on the installation of exhaust air heat pumps to the apartments and air source heat pumps to the houses.

All space heating and hot water will be provided to the buildings from renewable technologies. All systems are fuelled by mains electricity and therefore as the National Grid decarbonises so the homes will become zero carbon. The homes are zero carbon ready.

The Summary SAP Reports for the modelled homes are attached as Appendix 1

The total reduction in site carbon dioxide emissions from energy efficiency measures and low-carbon and renewable technologies can be summarised as follows;

	Total Emissions	% Reduction
	kg CO ₂ per year	
Baseline (Building Regulations TER)	51,607	
Be Green - after energy efficiency and Heat Pumps (DER)	19,724	61.78%

The water efficiency measures incorporated within the homes will ensure the water use is less than 110 litres per person per day and achieves the enhanced standard required by the Building Regulations (includes 5 l/p/d for external water use) and the planning policy.

The proposal meets the requirements of the adopted policy.

The key sustainability findings can be summarised as;

- ❖ Reduction in carbon dioxide emissions compared to the maximum permissible by the Building Regulations (Part L - 2021) through energy efficiency measures;
- ❖ A total reduction in (TER) carbon dioxide emissions of at least 50% from energy efficiency, low-carbon and renewable technologies will be achieved (based on Part L – 2021);
- ❖ The water use to each unit will achieve a standard of less than 110 litres per person per day;
- ❖ 31% of the homes will be 'affordable' and will be designed to be indistinguishable from other homes;
- ❖ Outdoor space in the form of private gardens and private communal spaces;
- ❖ High standards of environmental construction standards, a Site Waste Management Plan and other construction management principles;
- ❖ Secured by Design principles will be followed;
- ❖ All dwellings will be built in accordance with Part M4(1) of the Building Regulations and one home will meet full M4(3) compliance.

1.0 Introduction

This report has been commissioned by Merrow Wood and provides a Sustainability and Energy Statement in support of a detailed planning application for 48 dwellings (including affordable homes) on land north of Burleigh Lane, Crawley Down, West Sussex.

The Statement describes the methodology used in assessing the dwellings and the initiatives proposed.

The homes have been designed and will be constructed to reduce energy demand and carbon dioxide emissions.

The objective has been to reduce the energy demand to an economic minimum by making investments in the parts of the buildings that have the greatest impact on energy demand and are the most difficult and costly to change in the future, namely the building fabric.

Once cost-effective structures have been designed, low-carbon and renewable technologies have been considered to provide heat and/or electricity.

The following hierarchy has been followed:

- Lean reduce demand and consumption
- Clean increase energy efficiency
- Green provide low carbon renewable energy sources

The report has been prepared by Ivan Ball of Bluesky Unlimited who are sustainability consultants.

2.0 Planning Policy Context

National Policy

The UK Government published its sustainable development strategy in 1999 entitled “A better quality of life: A strategy for sustainable development in the UK”. This sets out four main objectives for sustainable development in the UK:

- Social progress that recognises the needs of everyone.
- Effective protection of the environment.
- Prudent use of natural resources.
- Maintenance of high stable levels of economic growth and employment.

Sustainable Communities: Building for the Future, known colloquially as the Communities Plan was published in 2003. The Plan sets out a long-term programme of action for delivering sustainable communities in both urban and rural areas. It aims to tackle housing supply issues in parts of the country, low demand in other parts and the quality of our public spaces. The Communities Plan describes sustainable communities as: Active, inclusive and safe, well run, environmentally sensitive, well designed and built, well connected, thriving, well served and fair for everyone.

The most relevant national planning policy guidance on sustainability is set out in:

- National Planning Policy Framework – December 2024

Paragraph 161 states;

‘The planning system should support the transition to net zero by 2050 and take full account of all climate impacts including overheating, water scarcity, storm and flood risks and coastal change. It should help to: shape places in ways that contribute to radical reductions in greenhouse gas emissions, minimise vulnerability and improve resilience; encourage the reuse of existing resources, including the conversion of existing buildings; and support renewable and low carbon energy and associated infrastructure.’

Local Policy

The planning policy is provided by the **Mid Sussex District Plan 2014-2031**, which was adopted in March 2018.

Of particular relevance to the topic area of this Statement is;

Policy DP39: Sustainable Design and Construction

All development proposals must seek to improve the sustainability of development and should where appropriate and feasible according to the type and size of development and location, incorporate the following measures:

- *Minimise energy use through the design and layout of the scheme including through the use of natural lighting and ventilation;*
- *Explore opportunities for efficient energy supply through the use of communal heating networks where viable and feasible;*
- *Use renewable sources of energy;*
- *Maximise efficient use of resources, including minimising waste and maximising recycling/ re-use of materials through both construction and occupation;*
- *Limit water use to 110 litres/person/day in accordance with Policy DP42: Water Infrastructure and the Water Environment;*
- *Demonstrate how the risks associated with future climate change have been planned for as part of the layout of the scheme and design of its buildings to ensure its longer-term resilience.*

DP42: Water Infrastructure and the Water Environment

New development proposals must be in accordance with the objectives of the Water Framework Directive, and accord with the findings of the Gatwick Sub Region Water Cycle Study with respect to water quality, water supply and wastewater treatment and consequently the optional requirement under Building Regulations – Part G applies to all new residential development in the district.

Development must meet the following water consumption standards:

- *Residential units should meet a water consumption standard of 110 litres per person per day (including external water use);*

The Council are working on their new plan, **Mid Sussex District Plan 2021-2039** and published the Submission Draft (Regulation 19) in December 2023.

3.0 Assessment Methodology and Targets

3.1 Methodology

The energy strategy uses a number of SAP calculations that have been prepared for representative unit types. The results have been aggregated across similar unit types to provide an accurate assessment of the total site emissions and allow different specification options, low-carbon and renewable technologies to be tested.

Emission Factors

The CO₂ emission factors, where applicable, used throughout this report have been taken from the Building Regulation Approved Document L - 2021.

	kg CO ₂ /kWh
Natural gas	0.210
Grid supplied and displaced electricity	0.136

3.2 Targets

The following targets have been crafted to enable compliance with current Building Regulations as well as National and Local planning policy.

Description of Target	Target/Scope
Climate Change	
Ensure that peak run off rates are no greater for the developed site than it was for the pre-development site.	Whole Site
In appropriate areas the use of porous surfaces and minimal hard ground surfaces will be implemented. All additional surface water generated will be attenuated and treated using SuDS prior to discharge.	Whole Site

Details are provided in the Flood Risk Assessment and Drainage Strategy, which accompanies the application.

Description of Target	Target/ Scope
Community	
All new units will be built in accordance with Part M4(1) of the Building Regulations.	All dwellings
Secured by Design principles will be followed. This will involve consultation with the Architectural Liaison Officer/ Crime Prevention Officer at the detailed design stage.	Whole Site

Description of Target	Target/ Scope
Transport and Movement	
Information will be provided in Home Owners Guide, giving details of frequency and location of public transport services.	Whole site
All dwellings will be provided with cycle storage.	Whole Site
All dwellings will be provided with access to an EV charging point.	Whole Site
A Travel Plan will be developed which will be used to promote and encourage sustainable forms of transport.	Whole Site

Details are provided in the Transport Assessment, which accompanies the application.

Description of Target	Target/ Scope
Ecology and Landscaping	
Any significant ecological features shall be retained and protected in line with the requirements of BS5837.	Whole site
A suitably qualified ecologist has been appointed to provide recommendations for ecological enhancement and these will be included in the landscaping design.	Whole site
A suitably qualified ecologist will be appointed to confirm that applicable legislation is being followed and to prepare a long-term management plan for the site.	Whole site
The overall level of biodiversity within the boundaries of the project shall be greater after the project is completed than was assessed by the ecologist before the project commenced.	Whole site

Details are provided in the Ecology Assessment, which accompanies the application.

Description of Target	Target/ Scope
Resources	
All materials used for the construction of the homes will be A+, A or B rated according to The Green Guide to Specification, unless deemed impractical or otherwise prescribed.	Whole Site
All timber for basic elements will be obtained from appropriately certified legal sources. In addition, 80% of building element timber will be procured from sustainably certified forests.	Whole Site
All kitchens will be fitted with internal recycling bins and dedicated external space (s) will be provided for recyclable storage accessible to all potential users.	Whole Site

Description of Target	Target/ Scope
Buildings	
Carbon dioxide emissions will be reduced by at least 50% to all homes through energy efficiency, low-carbon and renewable technologies.	All dwellings
All heating will be provided by renewable technologies and there will be no NO _x or CO ₂ emissions from the site. All homes will be zero carbon ready (when the National Grid decarbonises).	All dwellings
EU Labelling Information for white goods will be provided to all dwellings and where white goods are to be provided, they will be energy efficient.	All dwellings
100% of domestic fixed internal lighting is to be energy efficient.	All dwellings
The completed building fabric is to achieve air leakage rates of no greater than 4.0 m ³ /hr/m ² for the homes.	4.0 m ³ /hr/m ² for all dwellings
Sanitary fittings will be selected that minimise the consumption of mains water and all dwellings will achieve a water efficiency target of less than 110 l/p/d.	All dwellings to use less than 110 l/p/d

Description of Target	Target/ Scope
Construction Process and Site Management	
Waste arising from site will be monitored and segregated into at least five waste streams for recycling throughout the construction period.	Construction Site
All temporary timber (site hoardings, formwork, and scaffold boards) will be from FSC, CSA, SFI or PEFC sources, or re-used timber.	Construction Site

4.0 **Proposal**

The proposal is for the construction of 48 dwellings, comprising 1 and 2-bedroom apartments and 2, 3 and 4-bedroom terrace, semi-detached and detached houses. The accommodation schedule can be expressed as follows:

Unit Type	Number	Area	Area
		m ²	m ²
1-Bedroom Apartments	3	56.0	168.0
1-Bedroom Apartment	1	61.0	61.0
2-Bedroom Apartment	1	72.0	72.0
2-Bedroom Apartment	1	73.0	73.0
2-Bedroom Apartment	1	74.0	74.0
2-Bedroom Apartment	1	80.0	80.0
2-Bedroom Mid & End-terrace houses	4	80.0	320.0
2-Bedroom Apartment	1	81.0	81.0
3-Bedroom Mid & End-terrace house	2	96.0	192.0
2-Bedroom Semi-detached house	1	106.0	106.0
3-Bedroom Detached houses	3	109.0	327.0
3-Bedroom Detached house	5	110.0	550.0
4-Bedroom Mid & End-terrace & Detached houses	6	111.0	666.0
4-Bedroom End-terrace houses	3	114.0	342.0
3-Bedroom Semi-detached houses	4	115.0	460.0
4-Bedroom Detached houses	3	123.0	369.0
4-Bedroom Detached houses	4	135.0	540.0
4-Bedroom Detached houses	4	161.0	644.0
Total	48		5,125.0

5.0 Energy Efficiency

5.1 Demand Reduction (Be Lean and Be Clean)

Design

The energy performance of a building is affected by its design, construction and use and whilst occupant behaviour is beyond the remit of this statement, better design and construction methods can significantly reduce the life cycle emissions of a building and assist the occupant to reduce consumption.

Sustainable design is not just about incorporating renewable technologies; buildings should be designed at the outset to provide suitable environmental conditions for the occupants whilst also consuming as little energy as practical.

Passive Design Measures

The passive design measures proposed include;

(i) Passive Solar Gain

Passive measures include allowing for natural ventilation and exposed thermal mass coupled with high levels of insulation, air tightness and the control of solar gain.

The Illustrative Site Plan set out the majority of homes generally with either a north-south or east-west orientation. The design provides the majority of homes with access to direct sunlight throughout the day.

(ii) Natural Daylighting

The design of the site seeks to maximise the standard of natural daylighting to all units. This will create a high-quality internal environment, which will reduce the need for artificial lighting.

(iii) Efficient Building Fabric

a. Building Envelope

U-values of the building envelope must meet Building Regulations Part L (2021) standards and further improvements to U-values will reduce the building's heating requirements.

The construction type is currently unknown but the development is equally suited to a traditional load bearing brick and block construction or a timber-framed or other system build technique.

However, for the purposes of this assessment the following specification is assumed:

The ground floors will be insulated with at least 150mm of PIR insulation.

It is assumed the external walls are constructed in 350mm thick cavity wall construction with 150mm fully filled cavities.

The cold roofs will be insulated with 450mm of mineral wool insulation and any sloping ceilings and flat roofs with 150mm of PIR insulation.

Windows are proposed as double glazed with Low 'e' soft coat and argon filled.

It is proposed to set maximum limits for the elemental U-values as follows:

Element	Part L Limiting U-values	Proposed U-values	Proposed Improvement
	W/m ² K	W/m ² K	
Ground Floors	0.18	0.11	39%
External Walls	0.26	0.18	31%
Roofs (cold)	0.16	0.10	38%
Sloping Roofs, Dormers & Flat Roofs	0.16	0.13	19%
Windows and Glazed Doors	1.60	1.20	25%
Roof Windows	1.60	1.10	31%
External Doors	1.60	1.20	25%
'g' Value for Glazing			0.50

b. Air Leakage

Large amounts of heat are lost in winter through air leakage from a building (also referred to as infiltration or air permeability) often through poor sealing of joints and openings in the building.

The Building Regulations set a minimum standard for air permeability of 8 m³ of air per hour per m² of envelope area, at 50Pa. The SAP modelling has been based on achieving a 50% improvement over Building Regulations and will target a permeability of 4.0 m³/hr/m² for the homes.

c. Thermal Bridging

The significance of Thermal Bridging, as a potentially major source of fabric heat losses, is increasingly understood. Improving the U-values for the main building fabric without accurately addressing the Thermal Bridging is no longer an option and will not achieve the fabric energy efficiency and energy and CO₂ reduction targets set out in this strategy.

The thermal details for the buildings will be modelled at the detailed working drawing stage but for the purposes of this assessment the thermal details formulated by the Recognised Construction Details have been used. Any details not available on the RCD website will be modelled. These will enable the buildings to achieve the higher energy efficiency requirements of the Building Regulations.

The following table provides the values currently used within the modelled SAP calculations.

Reference	Location	PSI Value
		W/mK
E2	Other Lintels (including other steel lintels)	0.028
E3	Sill	0.024
E4	Jamb	0.019
E5	Ground Floor (Normal)	0.046
E6	Intermediate Floor	0.000
E7	Party Floor	0.036
E10	Eaves (Ceiling)	0.051
E12	Gable (Ceiling)	0.029
E16	Corner (normal)	0.037
E17	Corner (inverted)	-0.079
E18	Party Wall	0.041

d. Ventilation

As a result of increasing thermal efficiency and air tightness, Building Regulations Approved Document F was also revised in 2021 to address the possibility of overheating and poor air quality. The ventilation to the En-Suites and Bathrooms will be comprised of continuous extract ventilation as per System 3 criteria. This will reduce the number of external penetrations required to the building envelope.

Active Design Measures will include;

(i) Efficient Lighting and Controls

Throughout the scheme natural lighting will be optimised.

Part L of the Building Regulations requires all light fitting to have lamps with a minimum luminous efficacy of 80 light source lumens per circuit-watt. It is assumed this standard will be achieved.

(ii) Space Heating and Hot Water

The SAP modelling has been based upon the installation of exhaust air heat pumps to the apartments and air source heat pumps to the houses.

5.2 Low-Carbon and Renewable Technologies (Be Clean and Be Green)

The carbon dioxide emissions established above have been used to test the viability of various renewable and low-carbon technologies as follows.

The Government's Renewable Obligation defines renewable energy in the UK. The identified technologies are;

- Small hydro-electric
- Landfill and sewage gas
- Onshore and offshore wind
- Biomass
- Tidal and wave power
- Geothermal power
- Solar

The use of landfill or sewage gas, offshore wind or any form of hydroelectric power is not suitable for the site due to its location. The remaining technologies are considered below;

Wind

Wind turbines are available in various sizes from large rotors able to supply whole communities to small roof or wall-mounted units for individual dwellings.

The Government wind speed database predicts local wind speeds at Burleigh Lane to be 4.5 m/s at 10m above ground level and 5.3 m/s at 25m above ground level. This is below the level generally required for commercial investment in large wind turbines. In addition the land take, potential for noise and signal interference make a large wind turbine unsuitable for this development.

Roof mounted turbines could be used at the development to generate small but valuable amounts of renewable electricity but the small output and contribution to total emissions means any investment would be small and purely tokenism. The use of wind turbines will also have a detrimental aesthetic impact on the appearance of the development.

The use of wind turbines is not proposed.

Combined Heat and Power and Community Heating

Combined heat and power (CHP) also called co-generation is a de-centralised method of producing electricity from a fuel and 'capturing' the heat generated for use in buildings. The plant is essentially a small-scale electrical power station. The production and transportation of electricity via the National Grid is very inefficient with over 65% of the energy produced at the power station being lost to the atmosphere and through transportation.

CHP units are generally gas fuelled and generate electricity with heat being a by-product. The heat is usually used to meet the hot water load, which is fairly consistent throughout the year.

Historically CO₂ savings have been achieved because gas has been used to generate electricity and gas has had a lower emissions factor than electricity, However, with the de-carbonisation of the electricity grid the benefit of CHP is negated.

CHP is not proposed.

Ground Source Heat Pumps

Sub soil temperatures are reasonably constant and predictable in the UK, providing a store of the sun's energy throughout the year. Ground source heat pumps (GSHP) extract this low-grade heat and convert it to usable heat for space heating.

GSHP operates on a similar principle to refrigerators, transferring heat from a cool place to a warmer place. They operate most efficiently when providing space heating at a low temperature, typically via under floor heating or with low temperature radiators.

The installation of GSHPs to apartments is very complex and is not appropriate.

The houses have insufficient ground area to sustain a horizontal collection system and the installations would require a bore hole to each, which would be cost prohibitive.

The use of ground source heat pumps is not proposed.

Solar

(i) Solar Water Heating

Solar hot water panels use the suns energy to directly heat water circulating through panels or pipes. The technology is simple and easily understood by purchasers.

Solar hot water heating panels are based generally around two types, which are available being 'flat plate collectors' and 'evacuated tubes'. Flat plate collectors can achieve an output of up to 1,124 kWh/annum (Schuco) and evacuated tubes can achieve outputs up to 1,365 kWh/annum (Riomay).

Panels are traditionally roof mounted and for highest efficiencies should be mounted plus or minus 30 degrees of due south. Evacuated tubes can be laid horizontally on flat roofs but flat plate collectors are recommended for installation at an incline of 30 degrees.

The installation of exhaust air heat pumps and air source heat pumps reduces the emissions significantly and the installation of solar hot water heating panels would only increase the emissions reduction by a further 5-7%.

Solar hot water panels could be used to reduce emissions but the incremental increase in reductions does not represent good value when compared with other technologies.

Solar hot water heating panels are not proposed.

(ii) Photovoltaics

Photovoltaic panels (PV) provide clean silent electricity. They generate electricity during most daylight conditions although they are most efficient when exposed to direct sunlight or are orientated to face plus or minus 30 degrees of due south.

PV panels can be integrated into many different aspects of a development including roofs, walls, shading devices or architectural panels. The panels typically have an electrical warranty of 20-25 years and an expected system lifespan of 25-40 years.

The installation of exhaust air heat pumps and air source heat pumps reduces the emissions significantly and whilst photovoltaic panels could be installed to some homes without detrimentally impacting the aesthetics of the development, they are not proposed at this stage.

Air Source Heat Pumps (ASHP)

Air sourced heat pumps operate using the same reverse refrigeration cycle as ground source heat pumps; however, the initial heat energy is extracted from the external air rather than the ground.

The system works by transferring heat absorbed from the outside air to an indoor space using a wet central heating system to heat radiators or underfloor heating and provide domestic hot water. Heat pumps work similarly to a refrigerator in that they absorb heat and transfer it to another medium.

ASHPs use electricity and through a condenser/ evaporator system put out somewhere between 3.0 and 3.3 times as much energy as they require to run. ASHPs work well with low temperature systems.

The SAP modelling has been based on the installation of exhaust air heat pumps into the apartments and air source heat pumps to the houses.

5.3 Establishing Carbon Dioxide Emissions

SAP calculations have been prepared for representative unit types.

There are four, 1-bedroom apartments with floor area of 56.0 (3 units) and 61.0 m² (1 unit) and five, 2-bedroom apartments with floor areas in the range 72.0 to 81.0 m².

SAP calculations have been therefore been prepared for a 2-bedroom apartment at 72.0 m², which are proposed as representative of all apartments.

There are 17 no. mid-terrace, end-terrace and semi-detached houses with floor areas in the range of 80.0 to 115.0 m².

SAP calculations have been prepared for a 3-bedroom mid-terrace and end-terrace house at 111.0 m², which are proposed as representative of the mid-terrace and end-terrace/semi-detached houses respectively.

SAP calculations have been prepared for a 3-bedroom detached house at 111.0 m², which are proposed as representative of the 11 no. detached houses in the floor area range 109.0 – 111.0 m².

SAP calculations have been prepared for a detached unit at 123.0 m², which are proposed as representative of all the detached houses in the floor area range 123.0 – 135.0 m².

SAP calculations have been prepared for a detached unit at 161.0 m², which are proposed as representative of all the detached houses of this floor area.

The Summary SAP Reports for the modelling units are attached as Appendix 1 but the TER and DER emissions can be summarised as follows;

	CO ₂ TER	CO ₂ DER
	kg CO ₂ /m ² /yr	kg CO ₂ /m ² /yr
2-Bedroom Apartment @ 72.0 m ²	8.95	3.11
3-Bedroom Mid-terrace house @ 111.0 m ²	8.77	3.64
3-Bedroom End-terrace house @ 111.0 m ²	10.05	3.98
3-Bedroom Detached house @ 111.0 m ²	11.23	4.28
4-Bedroom Detached house @ 123.0 m ²	10.41	3.94
4-Bedroom Detached house @ 161.0 m ²	9.47	3.50

Summary

Using the above results, the emissions can be aggregated across similar unit types to arrive at the total site emissions.

The total emissions can be calculated as follows;

	Area	CO ₂ TER	CO ₂ DER
	m ²	kg/yr	kg/yr
1 & 2-Bedroom Apartments	609.0	5,451	1,894
2 & 3-Bedroom Mid-terrace houses (80.0 – 111.0 m ²)	478.0	4,192	1,740
2 & 3-Bedroom End-terr/Semi-det houses (80.0 – 115.0 m ²)	1,275.0	12,814	5,075
3-Bedroom Detached houses (109.0 – 111.0 m ²)	1,210.0	13,588	5,179
4-Bedroom Detached houses (123.0 & 135.0 m ²)	909.0	9,463	3,582
4-Bedroom Detached houses (161.0 m ²)	644.0	6,099	2,254
Totals	5,125	51,607	19,724

The total emissions allowable through the Building Regulations (TER) are calculated as:

- **51,607 kg CO₂ per year**

With total actual site emissions (DER) assessed as:

- **19,724 kg CO₂ per year**

The site carbon dioxide emissions are reduced by 31,884 kg CO₂ per year as a result of the energy efficiency measures and renewable technologies, which equates to a reduction of 61.78% of the TER emissions.

5.4 Summary of Calculations and Proposals for Low-carbon and Renewable Technologies

The application seeks detailed consent for the construction of 48 dwellings, comprising nine, 1 and 2-bedroom apartments and 39, 2, 3 and 4-bedroom terrace, semi-detached and detached houses.

SAP calculations have been prepared for representative homes built to the specification set out above including the installation of exhaust air heat pumps to all apartments and air source heat pumps to all houses. The results from the calculations have been aggregated across similar unit types to provide an assessment of the total site emissions.

Various technologies have been considered above and whilst wind turbines, combined heat and power, ground source heat pumps and solar hot water heating panels are not considered appropriate the use of photovoltaic panels and air source heat pumps are considered feasible, although the installation of photovoltaic panels are not considered at this stage.

Be Lean

The construction standards for the fabric of the buildings proposes U-values, which demonstrate good practice and improve upon those required by the Building Regulations. Air tightness standards are targeted at a 50% improvement upon the minimum required by the Building Regulations.

In addition, it is proposed to install energy efficiency mechanical and electrical services.

Be Clean and Be Green

As a result of the energy efficiency measures incorporated into the fabric specification of the homes and the installation of exhaust air heat pumps to the apartments and air source heat pumps to the houses the total emissions from the site based upon the maximum permissible by the Building Regulations (TER) are calculated as **51,607 kg CO₂ per year**, with actual (DER) emissions after energy efficiency measures and the installation of renewable technologies of **19,724 kg CO₂ per year**.

The emissions are reduced by a total of **31,883 kg CO₂ per year**, which equates to a reduction of **61.78%**.

All space heating and hot water will be provided to the homes from renewable technologies.

All systems to the homes are fuelled by mains electricity and therefore as the National Grid decarbonises so the homes will become zero carbon. The homes are zero carbon ready.

There will be no mains gas connection to the site and therefore there will be no on-site NOx or CO₂ emissions.

The proposal meets the requirements of the adopted policy.

6.0 Climate change adaption and Water resources

Sustainable Drainage Systems (SUDS)

The site lies within Flood Zone 1 and the risk of flooding is regarded as low.

Further details of the flood risk and the proposals for the disposal of surface water are set out within the Flood Risk Assessment and Drainage Strategy, which accompanies the application.

Surface Water Management

Consideration has been given to the use of grey water recycling. However, customer's resistance to the appearance of the recycled water and the cost of the systems does not currently make them a viable option. They have therefore not been included in the proposals.

Water efficiency measures

In excess of 20% of the UK's water is used domestically with over 50% of this used for flushing WCs and washing (source: Environment Agency). The majority of this comes from drinking quality standard or potable water.

The water efficiency measures included will ensure that the water use target of less than 110 litres per person per day is achieved.

Water efficient devices have been evaluated and will be installed. The specification of such devices will be considered at detailed design stage and each will be subject to an evaluation based on technical performance, cost and market appeal, together with compliance with the water use regulations.

The following devices will be incorporated within the apartments and houses:

- water efficient taps;
- water efficient toilets;
- low output showers;
- flow restrictors to manage water pressures to achieve optimum levels and
- water meters.

Below is a typical specification, which would achieve the 110 Litres per person per day target (including five litres per person per day allowance for external water use).

Schedule of Appliance Water Consumption		
Appliance	Flow rate or capacity	Total Litres
WC	6/3 litres dual flush	17.64
Basin	2.0 litres/min.	4.74
Shower	9.0 litres/min	39.33
Bath	175 litres	19.25
Sink	5.0 litres/min	12.56
Washing Machine	6.75 litres/kg	14.18
Dishwasher	1.25 litres/places	4.50
		112.20
	Normalisation Factor	0.91
	Total Internal Water Consumption	102.10
	External Water Use	5.00
	Total Water Consumption	107.10

7.0 Materials and Waste

The BRE Green Guide to Specification is a simple guide for design professionals. The guide provides environmental impact, cost and replacement interval information for a wide range of commonly used building specifications over a notional 60-year building life. The construction specification will prioritise materials within ratings A+, A or B.

Preference will be given to the use of local materials & suppliers where viable to reduce the transport distances and to support the local economy. A full evaluation of these suppliers will be undertaken at the next stage of design.

In addition, timber would be sourced, where practical, certified by PEFC or an equivalent approved certification body and all site timber used within the construction process would be recycled.

All insulation materials to will have a zero ozone depleting potential

Construction waste

Targets will be set to promote resource efficiency in accordance with guidance from WRAP, Envirowise, BRE and DEFRA.

The overarching principle of waste management is that waste should be treated or disposed of within the region where it is produced.

Construction operations generate waste materials as a result of general handling losses and surpluses. These wastes can be reduced through appropriate selection of the construction method, good site management practices and spotting opportunities to avoid creating unnecessary waste.

The Construction Strategy will explore these issues, some of which are set out below:

- Proper handling and storage of all materials to avoid damage.
- Efficient purchasing arrangements to minimise over ordering.
- Segregation of construction waste to maximise potential for reuse/recycling.
- Suppliers who collect and reuse/recycle packaging materials.

Appendix 1 – Summary SAP Reports for the Modelled Units

Summary for Input Data



Property Reference	Crawley Down 2BF TOP 74	Issued on Date	25/05/2025
Assessment Reference	Crawley Down 2BF TOP 74	Prop Type Ref	Crawley Down 2BF TOP 74
Property	Land North of Burleigh Lane, Crawley Down		
SAP Rating	88 B	DER	3.11
Environmental	98 A	% DER < TER	65.25
CO ₂ Emissions (t/year)	0.2	DFEE	21.05
Compliance Check	See BREL	% DFEE < TFEE	22.09
% DPER < TPER	29.21	DPER	32.77
TPER	46.29		

Assessor Details	Mr. Ivan Ball	Assessor ID	DE88-0001
Client			

SUMMARY FOR INPUT DATA FOR: New Build (As Designed)

Orientation	West
Property Tenure	2
Transaction Type	8
Terrain Type	Suburban
1.0 Property Type	Flat, End-Terrace
Position of Flat	Top-floor flat
Which Floor	2
2.0 Number of Storeys	1
3.0 Date Built	2025
4.0 Sheltered Sides	2
5.0 Sunlight/Shade	Average or unknown
6.0 Thermal Mass Parameter	Enter TMP value
Thermal Mass	250.00 kJ/m ² K

7.0 Electricity Tariff	Standard
Smart electricity meter fitted	Yes
Smart gas meter fitted	No

7.0 Measurements	Ground floor:	Heat Loss Perimeter	Internal Floor Area	Average Storey Height
		17.03 m	70.00 m ²	2.40 m

8.0 Living Area	31.00	m ²
-----------------	-------	----------------

9.0 External Walls	Description	Type	Construction	U-Value (W/m ² K)	Kappa (kJ/m ² K)	Gross Area(m ²)	Nett Area (m ²)	Shelter Res	Shelter	Openings	Area Calculation Type
	External Wall	Cavity Wall	Cavity wall : plasterboard on dabs, dense block, filled cavity, any outside structure	0.18	40.87	28.81	0.00	None	12.06	Enter Gross Area	

9.1 Party Walls	Description	Type	Construction	U-Value (W/m ² K)	Kappa (kJ/m ² K)	Area (m ²)	Shelter Res	Shelter	Shelter	
	Party Wall	Filled Cavity with Edge Sealing	Plasterboard on dabs mounted on cement render on both sides, AAC blocks, cavity	0.00	40.87	40.87	0.00	None	None	

10.0 External Roofs	Description	Type	Construction	U-Value (W/m ² K)	Kappa (kJ/m ² K)	Gross Area(m ²)	Nett Area (m ²)	Shelter Code	Shelter Factor	Shelter	Calculation Type	Openings
	Roof	External Plane Roof	Plasterboard, insulated at ceiling level	0.10	9.00	71.00	71.00	None	0.00	Enter Gross Area	0.00	

11.1 Party Floors	Description	Storey Index	Construction	Kappa (kJ/m ² K)	Area (m ²)
	Party Floor	Lowest occupied	Precast concrete plank floor (screed laid on rubber), carpeted	30.00	71.00

12.0 Opening Types	Description	Data Source	Type	Glazing	Glazing Gap	Filling Type	G-value	Frame Type	Frame Factor	U Value (W/m ² K)
--------------------	-------------	-------------	------	---------	-------------	--------------	---------	------------	--------------	------------------------------

Summary for Input Data

Windows & Glazed Doors	Manufacturer	Window	Double Low-E Soft 0.05	0.50	0.70	1.20												
13.0 Openings																		
Name	Opening Type	Location	Orientation	Area (m ²)	Pitch													
Kitchen/Dining	Windows & Glazed Doors	External Wall	South West	1.92														
Living	Windows & Glazed Doors	External Wall	South West	3.15														
Living	Windows & Glazed Doors	External Wall	South East	3.15														
Bedroom 1 & 2	Windows & Glazed Doors	External Wall	South East	3.84														
14.0 Conservatory																		
None																		
15.0 Draught Proofing																		
100 %																		
16.0 Draught Lobby																		
No																		
17.0 Thermal Bridging																		
Calculate Bridges																		
17.1 List of Bridges																		
Bridge Type	Source Type	Length	Psi	Adjusted Reference:	Imported													
E2 Other lintels (including other steel lintels)	Non Gov Approved Schemes	6.60	0.03	0.03	No													
E3 Sill	Non Gov Approved Schemes	3.60	0.02	0.02	No													
E4 Jamb	Non Gov Approved Schemes	18.00	0.02	0.02	No													
E18 Party wall between dwellings	Non Gov Approved Schemes	4.80	0.04	0.04	No													
E16 Corner (normal)	Non Gov Approved Schemes	2.40	0.04	0.04	No													
E7 Party floor between dwellings (in blocks of flats)	Non Gov Approved Schemes	17.03	0.04	0.04	No													
E11 Eaves (insulation at rafter level)	Non Gov Approved Schemes	17.03	0.04	0.04	No													
Y-value	0.02	W/m ² K																
19.0 Mechanical Ventilation																		
Mechanical Ventilation																		
Mechanical Ventilation System Present	No																	
20.0 Fans, Open Fireplaces, Flues																		
Number of open chimneys	0																	
Number of open flues	0																	
Number of chimneys/flues attached to closed fire	0																	
Number of flues attached to solid fuel boiler	0																	
Number of flues attached to other heater	0																	
Number of blocked chimneys	0																	
Number of intermittent extract fans	1																	
Number of passive vents	0																	
Number of flueless gas fires	0																	
21.0 Fixed Cooling System																		
No																		
22.0 Pressure Testing																		
Designed AP ₅₀	4.00 m ³ /(h.m ²) @ 50 Pa																	
Test Method	Blower Door																	
22.0 Lighting																		
No Fixed Lighting	<table border="1"> <tr> <td>No</td> <td>Name</td> <td>Efficacy</td> <td>Power</td> <td>Capacity</td> <td>Count</td> </tr> <tr> <td></td> <td>Lighting</td> <td>80.00</td> <td>5.00</td> <td>400.00</td> <td>28</td> </tr> </table>						No	Name	Efficacy	Power	Capacity	Count		Lighting	80.00	5.00	400.00	28
No	Name	Efficacy	Power	Capacity	Count													
	Lighting	80.00	5.00	400.00	28													
24.0 Main Heating 1																		
Percentage of Heat	Database																	
Database Ref. No.	100.00																	
Fuel Type	Electricity																	
In Winter	300.47																	
In Summer	220.69																	
Model Name	Fighter 470																	
Manufacturer	NIBE Energy Systems Ltd																	
System Type	Heat Pump																	
Controls SAP Code	2208																	
Is MHS Pumped	Pump in heated space																	

Summary for Input Data



Heating Pump Age	2013 or later											
Heat Emitter	Radiators											
Flow Temperature	Enter value											
Flow Temperature Value	45.00											
25.0 Main Heating 2	None											
26.0 Heat Networks	None											
27.0 Secondary Heating	None											
28.0 Water Heating												
Water Heating	Main Heating 1											
SAP Code	901											
Flue Gas Heat Recovery System	No											
Waste Water Heat Recovery Instantaneous System 1	No											
Waste Water Heat Recovery Instantaneous System 2	No											
Waste Water Heat Recovery Storage System	No											
Solar Panel	No											
Water use <= 125 litres/person/day	Yes											
Cold Water Source	From mains											
Bath Count	1											
Immersion Only Heating Hot Water	No											
28.3 Waste Water Heat Recovery System												
29.0 Hot Water Cylinder												
Insulation Type	Internal Store											
Cylinder Volume	170.00	L										
Loss	1.56	kWh/day										
In Airing Cupboard	No											
34.0 Small-scale Hydro	None											
Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec	
Recommendations												
Lower cost measures												
None												
Further measures to achieve even higher standards												
				Typical Cost	Typical savings per year				Ratings after improvement		Environmental Impact	
									SAP rating			Environmental Impact
									0			0
									0			0
									0			0

Summary for Input Data



Property Reference	Crawley Down 3BH MID 111	Issued on Date	25/05/2025
Assessment Reference	Crawley Down 3BH MID 111	Prop Type Ref	Crawley Down 3BH MID 111
Property	Land North of Burleigh Lane, Crawley Down		
SAP Rating	84 B	DER	3.64
Environmental	97 A	% DER < TER	58.49
CO ₂ Emissions (t/year)	0.36	DFEE	25.96
Compliance Check	See BREL	% DFEE < TFEE	4.87
% DPER < TPER	15.57	DPER	38.36
TPER	45.43		

Assessor Details	Mr. Ivan Ball	Assessor ID	DE88-0001
Client			

SUMMARY FOR INPUT DATA FOR: New Build (As Designed)

Orientation	North	
Property Tenure	1	
Transaction Type	6	
Terrain Type	Suburban	
1.0 Property Type	House, Mid-Terrace	
2.0 Number of Storeys	3	
3.0 Date Built	2025	
4.0 Sheltered Sides	2	
5.0 Sunlight/Shade	Average or unknown	
6.0 Thermal Mass Parameter	Enter TMP value	
Thermal Mass	250.00	kJ/m ² K
7.0 Electricity Tariff	Standard	
Smart electricity meter fitted	Yes	
Smart gas meter fitted	No	

7.0 Measurements		Heat Loss Perimeter	Internal Floor Area	Average Storey Height
Ground floor:		9.60 m	43.40 m ²	2.40 m
1st Storey:		9.60 m	36.97 m ²	2.40 m
2nd Storey:		9.60 m	28.92 m ²	2.32 m

8.0 Living Area	16.20	m ²
-----------------	-------	----------------

9.0 External Walls		Construction	U-Value (W/m ² K)	Kappa (kJ/m ² K)	Gross Area(m ²)	Nett Area (m ²)	Shelter Res	Shelter	Openings	Area Calculation Type
External Wall		Cavity wall : plasterboard on dabs, dense block, filled cavity, any outside structure	0.18	63.44	40.42	0.00	None	23.02	Enter Gross Area	

9.1 Party Walls		Construction	U-Value (W/m ² K)	Kappa (kJ/m ² K)	Area (m ²)	Shelter Res	Shelter
Party Wall	Filled Cavity with Edge Sealing	Plasterboard on dabs mounted on cement render on both sides, AAC blocks, cavity	0.00	106.82	None	None	None

10.0 External Roofs		Construction	U-Value (W/m ² K)	Kappa (kJ/m ² K)	Gross Area(m ²)	Nett Area (m ²)	Shelter Code	Shelter Factor	Calulation	Openings Type
External Roof	External Plane Roof	Plasterboard, insulated at ceiling level	0.10	9.00	33.83	33.83	None	0.00	Enter Gross Area	0.00
Sloping Ceilings	External Slope Roof	Plasterboard, insulated slope	0.13	9.00	13.14	13.14	None	0.00	Enter Gross Area	0.00
Flat Roof over Bay	External Flat Roof	Plasterboard, insulated flat roof	0.13	9.00	1.55	1.55	None	0.00	Enter Gross Area	0.00

11.0 Heat Loss Floors		Construction	U-Value (W/m ² K)	Shelter Code	Shelter Factor	Kappa (kJ/m ² K)	Area (m ²)
Ground Floor	Ground Floor - Solid Lowest occupied	Suspended concrete floor, carpeted	0.11	None	0.00	75.00	43.40

12.0 Opening Types

Summary for Input Data

Description	Data Source	Type	Glazing	Glazing Gap	Filling Type	G-value	Frame Type	Frame Factor	U Value (W/m ² K)
Windows & Glazed Doors External Doors	Manufacturer Manufacturer	Window Half Glazed Door	Double Low-E Soft 0.05 Double Low-E Soft 0.05			0.50 0.50		0.70 0.70	1.20 1.20
13.0 Openings									
Name Kitchen Entrance Hall Living Dining Bed 3 Bed 2 Bed 1 En Suite	Opening Type Windows & Glazed Doors External Doors Windows & Glazed Doors	Location External Wall External Wall External Wall External Wall External Wall External Wall External Wall	Orientation North North South South North South North South	Area (m ²) 2.97 2.32 1.02 5.25 3.75 3.75 2.52 1.44	Pitch				
14.0 Conservatory									
None									
15.0 Draught Proofing									
100 %									
16.0 Draught Lobby									
No									
17.0 Thermal Bridging									
Calculate Bridges									
17.1 List of Bridges									
Bridge Type E2 Other lintels (including other steel lintels) E3 Sill E4 Jamb E5 Ground floor (normal) E16 Corner (normal) E17 Corner (inverted – internal area greater than external area) E6 Intermediate floor within a dwelling E10 Eaves (insulation at ceiling level) E13 Gable (insulation at rafter level) E18 Party wall between dwellings E14 Flat roof	Source Type Non Gov Approved Schemes Non Gov Approved Schemes	Length 13.41 9.88 27.60 9.60 4.80 4.80 19.20 20.28 13.14 26.40 3.62	Psi 0.03 0.02 0.02 0.05 0.04 -0.08 0.00 0.05 0.03 0.04 0.04	Adjusted Reference: 0.03 0.02 0.02 0.05 0.04 -0.08 0.00 0.05 0.03 0.04 0.04	Imported No No No No No No No No No No No No No No No				
Y-value	0.03				W/m ² K				
19.0 Mechanical Ventilation									
Mechanical Ventilation									
Mechanical Ventilation System Present	No								
20.0 Fans, Open Fireplaces, Flues									
Number of open chimneys	0								
Number of open flues	0								
Number of chimneys/flues attached to closed fire	0								
Number of flues attached to solid fuel boiler	0								
Number of flues attached to other heater	0								
Number of blocked chimneys	0								
Number of intermittent extract fans	3								
Number of passive vents	0								
Number of flueless gas fires	0								
21.0 Fixed Cooling System									
No									
22.0 Pressure Testing									
Designed AP ₅₀	4.00				m ³ /(h.m ²) @ 50 Pa				
Test Method	Blower Door								
22.0 Lighting									
No Fixed Lighting	No								
	Name Lighting	Efficacy 80.00	Power 5.00	Capacity 400.00	Count 44				
24.0 Main Heating 1									
Percentage of Heat	Database								
Database Ref. No.	100.00				%				
Fuel Type	102607								
	Electricity								

Summary for Input Data



In Winter	263.55
In Summer	163.62
Model Name	aroTHERM 5kW
Manufacturer	Vaillant Group UK Ltd
System Type	Heat Pump
Controls SAP Code	2208
Is MHS Pumped	Pump in heated space
Heating Pump Age	2013 or later
Heat Emitter	Radiators
Flow Temperature	Enter value
Flow Temperature Value	45.00
25.0 Main Heating 2	None
26.0 Heat Networks	None
27.0 Secondary Heating	None
28.0 Water Heating	
Water Heating	Main Heating 1
SAP Code	901
Flue Gas Heat Recovery System	No
Waste Water Heat Recovery Instantaneous System 1	No
Waste Water Heat Recovery Instantaneous System 2	No
Waste Water Heat Recovery Storage System	No
Solar Panel	No
Water use <= 125 litres/person/day	Yes
Cold Water Source	From mains
Bath Count	1
Immersion Only Heating Hot Water	No
28.3 Waste Water Heat Recovery System	
29.0 Hot Water Cylinder	Hot Water Cylinder
Cylinder Stat	Yes
Cylinder In Heated Space	Yes
Independent Time Control	Yes
Insulation Type	Measured Loss
Cylinder Volume	250.00
Loss	1.68
Pipes insulation	All accessible pipework insulated
In Airing Cupboard	No
31.0 Thermal Store	None
34.0 Small-scale Hydro	None

Recommendations		Ratings after improvement	
		SAP rating	Environmental Impact
Lower cost measures	£4,000 - £6,000	B 86	A 97
None	£3,500 - £5,500	B 91	A 98
Further measures to achieve even higher standards		0	0

Summary for Input Data

Property Reference	Crawley Down 3BH END 111			Issued on Date	25/05/2025
Assessment Reference	Crawley Down 3BH END 111			Prop Type Ref	Crawley Down 3BH END 111
Property	Land North of Burleigh Lane, Crawley Down				
SAP Rating	82 B	DER	3.98	TER	10.05
Environmental	96 A	% DER < TER			60.40
CO ₂ Emissions (t/year)	0.4	DFEE	31.85	TFEE	33.69
Compliance Check	See BREL	% DFEE < TFEE			5.47
% DPER < TPER	20.13	DPER	41.78	TPER	52.31

Assessor Details	Mr. Ivan Ball	Assessor ID	DE88-0001
Client			

SUMMARY FOR INPUT DATA FOR: New Build (As Designed)

Orientation	North	
Property Tenure	1	
Transaction Type	6	
Terrain Type	Suburban	
1.0 Property Type	House, End-Terrace	
2.0 Number of Storeys	3	
3.0 Date Built	2025	
4.0 Sheltered Sides	2	
5.0 Sunlight/Shade	Average or unknown	
6.0 Thermal Mass Parameter	Enter TMP value	
Thermal Mass	250.00	kJ/m ² K
7.0 Electricity Tariff	Standard	
Smart electricity meter fitted	Yes	
Smart gas meter fitted	No	

7.0 Measurements		Heat Loss Perimeter	Internal Floor Area	Average Storey Height
Ground floor:		18.31 m	43.40 m ²	2.40 m
1st Storey:		17.34 m	36.97 m ²	2.40 m
2nd Storey:		17.34 m	28.92 m ²	2.32 m

8.0 Living Area	16.20	m ²
-----------------	-------	----------------

9.0 External Walls		Construction	U-Value (W/m ² K)	Kappa (kJ/m ² K)	Gross Area(m ²)	Nett Area (m ²)	Shelter Res	Shelter	Openings	Area Calculation Type
External Wall		Cavity wall : plasterboard on dabs, dense block, filled cavity, any outside structure	0.18	116.85	90.00	0.00	None	None	26.85	Enter Gross Area

9.1 Party Walls		Construction	U-Value (W/m ² K)	Kappa (kJ/m ² K)	Area (m ²)	Shelter Res	Shelter
Party Wall	Filled Cavity with Edge Sealing	Plasterboard on dabs mounted on cement render on both sides, AAC blocks, cavity	0.00	53.41	53.41	None	None

10.0 External Roofs		Construction	U-Value (W/m ² K)	Kappa (kJ/m ² K)	Gross Area(m ²)	Nett Area (m ²)	Shelter Code	Shelter Factor	Calulation	Openings Type
External Roof	External Plane Roof	Plasterboard, insulated at ceiling level	0.10	9.00	33.83	33.83	None	0.00	Enter Gross Area	0.00
Sloping Ceilings	External Slope Roof	Plasterboard, insulated slope	0.13	9.00	13.14	11.79	None	0.00	Enter Gross Area	1.35
Flat Roof over Bay	External Flat Roof	Plasterboard, insulated flat roof	0.13	9.00	1.55	1.55	None	0.00	Enter Gross Area	0.00

11.0 Heat Loss Floors		Construction	U-Value (W/m ² K)	Shelter Code	Shelter Factor	Kappa (kJ/m ² K)	Area (m ²)
Ground Floor	Ground Floor - Solid Lowest occupied	Suspended concrete floor, carpeted	0.11	None	0.00	75.00	43.40

12.0 Opening Types

Summary for Input Data



Description	Data Source	Type	Glazing	Glazing Gap	Filling Type	G-value	Frame Type	Frame Factor	U Value (W/m²K)									
Windows & Glazed Doors	Manufacturer	Window	Double Low-E Soft 0.05			0.50		0.70	1.20									
External Doors	Manufacturer	Half Glazed Door	Double Low-E Soft 0.05			0.50		0.70	1.20									
Roof Window	Manufacturer	Roof Window	Double Low-E Soft 0.05			0.50		0.70	1.10									
13.0 Openings																		
Name	Opening Type	Location	Orientation	Area (m²)		Pitch												
Kitchen	Windows & Glazed Doors	External Wall	North	2.97														
Entrance Hall	External Doors	External Wall	North	2.32														
Living	Windows & Glazed Doors	External Wall	South	1.02														
Dining	Windows & Glazed Doors	External Wall	South	5.25														
Bed 3	Windows & Glazed Doors	External Wall	North	3.75														
Bed 2	Windows & Glazed Doors	External Wall	South	3.75														
Bed 1	Windows & Glazed Doors	External Wall	North	2.52														
En Suite	Windows & Glazed Doors	External Wall	South	1.44														
WC/Utility	Windows & Glazed Doors	External Wall	East	1.02														
Bath	Windows & Glazed Doors	External Wall	East	0.71														
Bed 1	Roof Window	Sloping Ceilings	East	1.35														
Staircase	Windows & Glazed Doors	External Wall	West	2.10														
14.0 Conservatory																		
None																		
15.0 Draught Proofing																		
100																		
16.0 Draught Lobby																		
No																		
17.0 Thermal Bridging																		
Calculate Bridges																		
17.1 List of Bridges																		
Bridge Type	Source Type	Length	Psi	Adjusted Reference:			Imported											
E2 Other lintels (including other steel lintels)	Non Gov Approved Schemes	16.77	0.03	0.03			No											
E3 Sill	Non Gov Approved Schemes	13.24	0.02	0.02			No											
E4 Jamb	Non Gov Approved Schemes	27.60	0.02	0.02			No											
E5 Ground floor (normal)	Non Gov Approved Schemes	18.31	0.05	0.05			No											
E16 Corner (normal)	Non Gov Approved Schemes	18.00	0.04	0.04			No											
E17 Corner (inverted – internal area greater than external area)	Non Gov Approved Schemes	4.80	-0.08	-0.08			No											
E6 Intermediate floor within a dwelling	Non Gov Approved Schemes	34.68	0.00	0.00			No											
E10 Eaves (insulation at ceiling level)	Non Gov Approved Schemes	20.28	0.05	0.05			No											
E13 Gable (insulation at rafter level)	Non Gov Approved Schemes	13.14	0.03	0.03			No											
E18 Party wall between dwellings	Non Gov Approved Schemes	13.20	0.04	0.04			No											
E14 Flat roof	Non Gov Approved Schemes	3.62	0.04	0.04			No											
Y-value	0.02			W/m²K														
19.0 Mechanical Ventilation																		
Mechanical Ventilation																		
Mechanical Ventilation System Present	No																	
20.0 Fans, Open Fireplaces, Flues																		
Number of open chimneys	0																	
Number of open flues	0																	
Number of chimneys/flues attached to closed fire	0																	
Number of flues attached to solid fuel boiler	0																	
Number of flues attached to other heater	0																	
Number of blocked chimneys	0																	
Number of intermittent extract fans	3																	
Number of passive vents	0																	
Number of flueless gas fires	0																	
21.0 Fixed Cooling System																		
No																		
22.0 Pressure Testing																		
Designed AP ₅₀	4.00			m ³ /(h.m ²) @ 50 Pa														
Test Method	Blower Door																	
22.0 Lighting																		
No Fixed Lighting	No																	
	Name	Efficacy	Power	Capacity		Count												
	Lighting	80.00	5.00	400.00		44												
24.0 Main Heating 1																		
Database	100.00			% %														
Percentage of Heat																		

Summary for Input Data

Database Ref. No.	102607										
Fuel Type	Electricity										
In Winter	260.97										
In Summer	163.68										
Model Name	aroTHERM 5kW										
Manufacturer	Vaillant Group UK Ltd										
System Type	Heat Pump										
Controls SAP Code	2208										
Is MHS Pumped	Pump in heated space										
Heating Pump Age	2013 or later										
Heat Emitter	Radiators										
Flow Temperature	Enter value										
Flow Temperature Value	45.00										
25.0 Main Heating 2	None										
26.0 Heat Networks	None										
27.0 Secondary Heating	None										
28.0 Water Heating											
Water Heating	Main Heating 1										
SAP Code	901										
Flue Gas Heat Recovery System	No										
Waste Water Heat Recovery Instantaneous System 1	No										
Waste Water Heat Recovery Instantaneous System 2	No										
Waste Water Heat Recovery Storage System	No										
Solar Panel	No										
Water use <= 125 litres/person/day	Yes										
Cold Water Source	From mains										
Bath Count	1										
Immersion Only Heating Hot Water	No										
28.3 Waste Water Heat Recovery System											
29.0 Hot Water Cylinder	Hot Water Cylinder										
Cylinder Stat	Yes										
Cylinder In Heated Space	Yes										
Independent Time Control	Yes										
Insulation Type	Measured Loss										
Cylinder Volume	250.00										
Loss	1.68										
Pipes insulation	All accessible pipework insulated										
In Airing Cupboard	No										
31.0 Thermal Store	None										
34.0 Small-scale Hydro	None										
Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec

Recommendations
Lower cost measures

None

Further measures to achieve even higher standards

Typical Cost	Typical savings per year	Ratings after improvement
£4,000 - £6,000	£110	SAP rating
£3,500 - £5,500	£245	B 84
		B 90
		A 97
		A 98

Summary for Input Data



0

0

Summary for Input Data



Property Reference	Crawley Down 3BH DET 111	Issued on Date	25/05/2025
Assessment Reference	Crawley Down 3BH DET 111	Prop Type Ref	Crawley Down 3BH DET 111
Property	Land North of Burleigh Lane, Crawley Down		
SAP Rating	81 B	DER	4.28
Environmental	96 A	% DER < TER	61.89
CO ₂ Emissions (t/year)	0.42	DFEE	36.67
Compliance Check	See BREL	% DFEE < TFEE	6.07
% DPER < TPER	23.53	DPER	44.86
Assessor Details	Mr. Ivan Ball	Assessor ID	DE88-0001
Client			

SUMMARY FOR INPUT DATA FOR: New Build (As Designed)

Orientation	North
Property Tenure	1
Transaction Type	6
Terrain Type	Suburban
1.0 Property Type	House, Detached
2.0 Number of Storeys	3
3.0 Date Built	2025
4.0 Sheltered Sides	2
5.0 Sunlight/Shade	Average or unknown
6.0 Thermal Mass Parameter	Enter TMP value
Thermal Mass	250.00
	kJ/m ² K
7.0 Electricity Tariff	Standard
Smart electricity meter fitted	Yes
Smart gas meter fitted	No

7.0 Measurements		Heat Loss Perimeter	Internal Floor Area	Average Storey Height
Ground floor:		18.31 m	43.40 m ²	2.40 m
1st Storey:		17.34 m	36.97 m ²	2.40 m
2nd Storey:		17.34 m	28.92 m ²	2.32 m

8.0 Living Area	16.20	m ²
-----------------	-------	----------------

9.0 External Walls		Construction	U-Value (W/m ² K)	Kappa (kJ/m ² K)	Gross Area(m ²)	Nett Area (m ²)	Shelter Res	Shelter	Openings	Area Calculation Type
External Wall		Cavity wall : plasterboard on dabs, dense block, filled cavity, any outside structure	0.18	170.26	143.41	0.00	None	26.85	Enter Gross Area	

10.0 External Roofs		Construction	U-Value (W/m ² K)	Kappa (kJ/m ² K)	Gross Area(m ²)	Nett Area (m ²)	Shelter Code	Shelter Factor	Shelter Calculation	Openings Type
External Roof		External Plane Roof	Plasterboard, insulated at ceiling level		0.10	9.00	33.83	33.83	None	0.00 Enter Gross Area
Sloping Ceilings		External Slope Roof	Plasterboard, insulated slope		0.13	9.00	13.14	11.79	None	0.00 Enter Gross Area
Flat Roof over Bay		External Flat Roof	Plasterboard, insulated flat roof		0.13	9.00	1.55	1.55	None	0.00 Enter Gross Area

11.0 Heat Loss Floors		Construction	U-Value (W/m ² K)	Shelter Code	Shelter Factor	Kappa (kJ/m ² K)	Area (m ²)
Ground Floor		Ground Floor - Solid Lowest occupied	Suspended concrete floor, carpeted	None	0.00	75.00	43.40

12.0 Opening Types		Type	Glazing	Glazing Gap	Filling Type	G-value	Frame Type	Frame Factor	U Value (W/m ² K)
Windows & Glazed Doors	Manufacturer	Window	Double Low-E Soft 0.05			0.50	0.70	1.20	1.20
External Doors	Manufacturer	Half Glazed Door	Double Low-E Soft 0.05			0.50	0.70	1.20	1.20
Roof Window	Manufacturer	Roof Window	Double Low-E Soft 0.05			0.50	0.70	1.10	1.10

13.0 Openings

Summary for Input Data

Name	Opening Type	Location	Orientation	Area (m ²)	Pitch
Kitchen	Windows & Glazed Doors	External Wall	North	2.97	
Entrance Hall	External Doors	External Wall	North	2.32	
Living	Windows & Glazed Doors	External Wall	South	1.02	
Dining	Windows & Glazed Doors	External Wall	South	5.25	
Bed 3	Windows & Glazed Doors	External Wall	North	3.75	
Bed 2	Windows & Glazed Doors	External Wall	South	3.75	
Bed 1	Windows & Glazed Doors	External Wall	North	2.52	
En Suite	Windows & Glazed Doors	External Wall	South	1.44	
WC/Utility	Windows & Glazed Doors	External Wall	East	1.02	
Bath	Windows & Glazed Doors	External Wall	East	0.71	
Bed 1	Roof Window	Sloping Ceilings	East	1.35	
Staircase	Windows & Glazed Doors	External Wall	West	2.10	45

14.0 Conservatory	None	
15.0 Draught Proofing	100	%
16.0 Draught Lobby	No	

17.0 Thermal Bridging	Calculate Bridges
------------------------------	-------------------

17.1 List of Bridges					
Bridge Type					
E2 Other lintels (including other steel lintels)	Source Type	Length	Psi	Adjusted Reference:	Imported
E3 Sill	Non Gov Approved Schemes	16.77	0.03	0.03	No
E4 Jamb	Non Gov Approved Schemes	13.24	0.02	0.02	No
E5 Ground floor (normal)	Non Gov Approved Schemes	27.60	0.02	0.02	No
E16 Corner (normal)	Non Gov Approved Schemes	27.02	0.05	0.05	No
E17 Corner (inverted – internal area greater than external area)	Non Gov Approved Schemes	31.20	0.04	0.04	No
E6 Intermediate floor within a dwelling	Non Gov Approved Schemes	4.80	-0.08	-0.08	No
E10 Eaves (insulation at ceiling level)	Non Gov Approved Schemes	50.16	0.00	0.00	No
E13 Gable (insulation at rafter level)	Non Gov Approved Schemes	20.28	0.05	0.05	No
E14 Flat roof	Non Gov Approved Schemes	13.14	0.03	0.03	No
	Non Gov Approved Schemes	3.62	0.04	0.04	No

Y-value	0.02	W/m ² K
---------	------	--------------------

19.0 Mechanical Ventilation	
Mechanical Ventilation	
Mechanical Ventilation System Present	No

20.0 Fans, Open Fireplaces, Flues	
Number of open chimneys	0
Number of open flues	0
Number of chimneys/flues attached to closed fire	0
Number of flues attached to solid fuel boiler	0
Number of flues attached to other heater	0
Number of blocked chimneys	0
Number of intermittent extract fans	3
Number of passive vents	0
Number of flueless gas fires	0

21.0 Fixed Cooling System	No
----------------------------------	----

22.0 Pressure Testing	Yes	
Designed AP ₅₀	4.00	m ³ /(h.m ²) @ 50 Pa
Test Method	Blower Door	

22.0 Lighting					
No Fixed Lighting	No				
	Name	Efficacy	Power	Capacity	Count
	Lighting	80.00	5.00	400.00	44

24.0 Main Heating 1	Database	
Percentage of Heat	100.00	%
Database Ref. No.	102607	
Fuel Type	Electricity	
In Winter	259.14	
In Summer	163.74	

Summary for Input Data

Model Name	aroTHERM 5kW										
Manufacturer	Vaillant Group UK Ltd										
System Type	Heat Pump										
Controls SAP Code	2208										
Is MHS Pumped	Pump in heated space										
Heating Pump Age	2013 or later										
Heat Emitter	Radiators										
Flow Temperature	Enter value										
Flow Temperature Value	45.00										
<hr/>											
25.0 Main Heating 2	None										
<hr/>											
26.0 Heat Networks	None										
<hr/>											
27.0 Secondary Heating	None										
<hr/>											
28.0 Water Heating											
Water Heating	Main Heating 1										
SAP Code	901										
Flue Gas Heat Recovery System	No										
Waste Water Heat Recovery Instantaneous System 1	No										
Waste Water Heat Recovery Instantaneous System 2	No										
Waste Water Heat Recovery Storage System	No										
Solar Panel	No										
Water use <= 125 litres/person/day	Yes										
Cold Water Source	From mains										
Bath Count	1										
Immersion Only Heating Hot Water	No										
<hr/>											
28.3 Waste Water Heat Recovery System											
29.0 Hot Water Cylinder	Hot Water Cylinder										
Cylinder Stat	Yes										
Cylinder In Heated Space	Yes										
Independent Time Control	Yes										
Insulation Type	Measured Loss										
Cylinder Volume	250.00	L									
Loss	1.68	kWh/day									
Pipes insulation	All accessible pipework insulated										
In Airing Cupboard	No										
<hr/>											
31.0 Thermal Store	None										
<hr/>											
34.0 Small-scale Hydro	None										
Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
<hr/>											
Recommendations											
Lower cost measures											
None											
Further measures to achieve even higher standards											
				Typical Cost	Typical savings per year			Ratings after improvement		Environmental Impact	
				£4,000 - £6,000	£110			B 83	A 96		
				£3,500 - £5,500	£246			B 89	A 97		
								0	0		

Summary for Input Data



Property Reference	Crawley Down 4BH DET 123			Issued on Date	25/05/2025
Assessment Reference	Crawley Down 4BH DET 123			Prop Type Ref	Crawley Down 4BH DET 123
Property	Land North of Burleigh Lane, Crawley Down				
SAP Rating	82 B	DER	3.94	TER	10.41
Environmental	96 A	% DER < TER			62.15
CO ₂ Emissions (t/year)	0.44	DFEE	39.17	TFEE	41.20
Compliance Check	See BREL	% DFEE < TFEE			4.93
% DPER < TPER	24.17	DPER	41.23	TPER	54.38

Assessor Details	Mr. Ivan Ball	Assessor ID	DE88-0001
Client			

SUMMARY FOR INPUT DATA FOR: New Build (As Designed)

Orientation	North	
Property Tenure	1	
Transaction Type	6	
Terrain Type	Suburban	
1.0 Property Type	House, Detached	
2.0 Number of Storeys	2	
3.0 Date Built	2025	
4.0 Sheltered Sides	2	
5.0 Sunlight/Shade	Average or unknown	
6.0 Thermal Mass Parameter	Enter TMP value	
Thermal Mass	250.00	kJ/m ² K
7.0 Electricity Tariff	Standard	
Smart electricity meter fitted	Yes	
Smart gas meter fitted	No	

7.0 Measurements		Ground floor:	Heat Loss Perimeter	Internal Floor Area	Average Storey Height
		1st Storey:	33.55 m 31.66 m	62.71 m ² 60.35 m ²	2.40 m 2.40 m

8.0 Living Area	15.50	m ²
-----------------	-------	----------------

Description	Type	Construction	U-Value (W/m ² K)	Kappa (kJ/m ² K)	Gross Area(m ²)	Nett Area (m ²)	Shelter Res	Shelter	Openings	Area Calculation Type
External Wall	Cavity Wall	Cavity wall : plasterboard on dabs, dense block, filled cavity, any outside structure	0.18	156.50	119.26	0.00	None	37.24	Enter Gross Area	

10.0 External Roofs		Construction	U-Value (W/m ² K)	Kappa (kJ/m ² K)	Gross Area(m ²)	Nett Area (m ²)	Shelter Code	Shelter Factor	Calculation	Openings Type
External Roof		External Plane Roof	Plasterboard, insulated at ceiling level		0.10	9.00	60.35	60.35	None	0.00 Enter Gross Area
Flat Roof over Bay		External Flat Roof	Plasterboard, insulated flat roof		0.13	9.00	1.89	1.89	None	0.00 Enter Gross Area

Description	Type	Storey Index	Construction	U-Value (W/m ² K)	Shelter Code	Shelter Factor	Kappa (kJ/m ² K)	Area (m ²)
Ground Floor	Ground Floor - Solid	Lowest occupied	Suspended concrete floor, carpeted	0.11	None	0.00	75.00	62.71

12.0 Opening Types		Type	Glazing	Glazing Gap	Filling Type	G-value	Frame Type	Frame Factor	U Value (W/m ² K)
Windows & Glazed Doors	Manufacturer	Window	Double Low-E Soft	0.05		0.50		0.70	1.20
External Doors	Manufacturer	Half Glazed Door	Double Low-E Soft	0.05		0.50		0.70	1.20

Name	Opening Type	Location	Orientation	Area (m ²)	Pitch
Study & Dining	Windows & Glazed Doors	External Wall	North	5.76	
Entrance Hall	External Doors	External Wall	North	2.32	
WC	Windows & Glazed Doors	External Wall	North	0.92	

Summary for Input Data

Dining	Windows & Glazed Doors	External Wall	West	5.25	
Kitchen	Windows & Glazed Doors	External Wall	West	0.82	
Utility	Windows & Glazed Doors	External Wall	South	2.16	
Living	Windows & Glazed Doors	External Wall	South	0.99	
Living	Windows & Glazed Doors	External Wall	East	4.12	
Living	Windows & Glazed Doors	External Wall	North	0.99	
Bed 3 & 4	Windows & Glazed Doors	External Wall	North	4.32	
Bath	Windows & Glazed Doors	External Wall	North	0.71	
Bed 2 & 4	Windows & Glazed Doors	External Wall	West	4.80	
En Suite	Windows & Glazed Doors	External Wall	South	0.71	
Bed 1	Windows & Glazed Doors	External Wall	East	3.36	
14.0 Conservatory	None				
15.0 Draught Proofing	100		%		
16.0 Draught Lobby	No				
17.0 Thermal Bridging	Calculate Bridges				
17.1 List of Bridges					
Bridge Type	Source Type	Length	Psi	Adjusted Reference:	Imported
E2 Other lintels (including other steel lintels)	Non Gov Approved Schemes	22.18	0.03	0.03	No
E3 Sill	Non Gov Approved Schemes	16.02	0.02	0.02	No
E4 Jamb	Non Gov Approved Schemes	48.30	0.02	0.02	No
E5 Ground floor (normal)	Non Gov Approved Schemes	33.55	0.05	0.05	No
E16 Corner (normal)	Non Gov Approved Schemes	24.00	0.04	0.04	No
E17 Corner (inverted – internal area greater than external area)	Non Gov Approved Schemes	4.80	-0.08	-0.08	No
E6 Intermediate floor within a dwelling	Non Gov Approved Schemes	31.66	0.00	0.00	No
E10 Eaves (insulation at ceiling level)	Non Gov Approved Schemes	18.70	0.05	0.05	No
E13 Gable (insulation at rafter level)	Non Gov Approved Schemes	12.98	0.03	0.03	No
E14 Flat roof	Non Gov Approved Schemes	4.18	0.04	0.04	No
Y-value	0.02				W/m ² K
19.0 Mechanical Ventilation					
Mechanical Ventilation					
Mechanical Ventilation System Present	No				
20.0 Fans, Open Fireplaces, Flues					
Number of open chimneys	0				
Number of open flues	0				
Number of chimneys/flues attached to closed fire	0				
Number of flues attached to solid fuel boiler	0				
Number of flues attached to other heater	0				
Number of blocked chimneys	0				
Number of intermittent extract fans	3				
Number of passive vents	0				
Number of flueless gas fires	0				
21.0 Fixed Cooling System	No				
22.0 Pressure Testing	Yes				
Designed AP ₅₀	4.00				m ³ /(h.m ²) @ 50 Pa
Test Method	Blower Door				
22.0 Lighting					
No Fixed Lighting	No				
	Name Lighting	Efficacy 80.00	Power 5.00	Capacity 400.00	Count 52
24.0 Main Heating 1	Database				
Percentage of Heat	100.00		%		
Database Ref. No.	102615				
Fuel Type	Electricity				
In Winter	280.11				
In Summer	173.62				
Model Name	aroTHERM 8kW				

Summary for Input Data

Manufacturer	Vaillant Group UK Ltd										
System Type	Heat Pump										
Controls SAP Code	2208										
Is MHS Pumped	Pump in heated space										
Heating Pump Age	2013 or later										
Heat Emitter	Radiators										
Flow Temperature	Enter value										
Flow Temperature Value	45.00										
25.0 Main Heating 2	None										
26.0 Heat Networks	None										
27.0 Secondary Heating	None										
28.0 Water Heating											
Water Heating	Main Heating 1										
SAP Code	901										
Flue Gas Heat Recovery System	No										
Waste Water Heat Recovery Instantaneous System 1	No										
Waste Water Heat Recovery Instantaneous System 2	No										
Waste Water Heat Recovery Storage System	No										
Solar Panel	No										
Water use <= 125 litres/person/day	Yes										
Cold Water Source	From mains										
Bath Count	1										
Immersion Only Heating Hot Water	No										
28.3 Waste Water Heat Recovery System											
29.0 Hot Water Cylinder											
Cylinder Stat	Hot Water Cylinder										
Cylinder In Heated Space	Yes										
Independent Time Control	Yes										
Insulation Type	Measured Loss										
Cylinder Volume	250.00	L									
Loss	1.68	kWh/day									
Pipes insulation	All accessible pipework insulated										
In Airing Cupboard	No										
31.0 Thermal Store	None										
34.0 Small-scale Hydro	None										
Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
Recommendations											
Lower cost measures											
None											
Further measures to achieve even higher standards											
				Typical Cost	Typical savings per year			Ratings after improvement		Environmental Impact	
				£4,000 - £6,000 £3,500 - £5,500	£103 £250			SAP rating	B 84 B 89 0	A 97 A 98 0	

Summary for Input Data



Property Reference	Crawley Down 4BH DET 161	Issued on Date	25/05/2025
Assessment Reference	Crawley Down 4BH DET 161	Prop Type Ref	Crawley 4BH DET 161
Property	Land North of Burleigh Lane, Crawley Down		
SAP Rating	83 B	DER	3.50
Environmental	96 A	% DER < TER	63.04
CO ₂ Emissions (t/year)	0.51	DFEE	39.82
Compliance Check	See BREL	% DFEE < TFEE	41.65
% DPER < TPER	26.61	DPER	36.47
TPER	49.69		

Assessor Details	Mr. Ivan Ball	Assessor ID	DE88-0001
Client			

SUMMARY FOR INPUT DATA FOR: New Build (As Designed)

Orientation	West	
Property Tenure	1	
Transaction Type	6	
Terrain Type	Suburban	
1.0 Property Type	House, Detached	
2.0 Number of Storeys	2	
3.0 Date Built	2025	
4.0 Sheltered Sides	2	
5.0 Sunlight/Shade	Average or unknown	
6.0 Thermal Mass Parameter	Enter TMP value	
Thermal Mass	250.00	kJ/m ² K
7.0 Electricity Tariff	Standard	
Smart electricity meter fitted	Yes	
Smart gas meter fitted	No	

7.0 Measurements		Ground floor: 45.49 m	Heat Loss Perimeter	Internal Floor Area	Average Storey Height
		1st Storey: 43.41 m		82.09 m ² 79.39 m ²	2.40 m 2.40 m

8.0 Living Area	18.60	m ²
-----------------	-------	----------------

Description	Type	Construction	U-Value (W/m ² K)	Kappa (kJ/m ² K)	Gross Area(m ²)	Nett Area (m ²)	Shelter Res	Shelter	Openings	Area Calculation Type
External Wall	Cavity Wall	Cavity wall : plasterboard on dabs, dense block, filled cavity, any outside structure	0.18	213.36	162.86	0.00	None	50.50	Enter Gross Area	

10.0 External Roofs		Construction	U-Value (W/m ² K)	Kappa (kJ/m ² K)	Gross Area(m ²)	Nett Area (m ²)	Shelter Code	Shelter Factor	Calculation	Openings Type
External Roof		External Plane Roof	Plasterboard, insulated at ceiling level		0.10	9.00	79.39	79.39	None	0.00 Enter Gross Area
Flat Roof over Bay		External Flat Roof	Plasterboard, insulated flat roof		0.13	9.00	2.70	2.70	None	0.00 Enter Gross Area

Description	Type	Storey Index	Construction	U-Value (W/m ² K)	Shelter Code	Shelter Factor	Kappa (kJ/m ² K)	Area (m ²)
Ground Floor	Ground Floor - Solid	Lowest occupied	Suspended concrete floor, carpeted	0.11	None	0.00	75.00	82.09

12.0 Opening Types		Type	Glazing	Glazing Gap	Filling Type	G-value	Frame Type	Frame Factor	U Value (W/m ² K)
Windows & Glazed Doors	Manufacturer	Window	Double Low-E Soft	0.05		0.50		0.70	1.20
External Doors	Manufacturer	Half Glazed Door	Double Low-E Soft	0.05		0.50		0.70	1.20

Name	Opening Type	Location	Orientation	Area (m ²)	Pitch
Living	Windows & Glazed Doors	External Wall	North	0.99	
Living	Windows & Glazed Doors	External Wall	West	4.12	
Living	Windows & Glazed Doors	External Wall	South	0.99	

Summary for Input Data

Entrance Hall	External Doors	External Wall	West	2.32
WC	Windows & Glazed Doors	External Wall	North	0.50
Study	Windows & Glazed Doors	External Wall	West	3.60
Dining	Windows & Glazed Doors	External Wall	South	3.60
Kitchen	Windows & Glazed Doors	External Wall	South	1.08
Utility	External Doors	External Wall	East	2.16
Kitchen	Windows & Glazed Doors	External Wall	North	6.72
Living	Windows & Glazed Doors	External Wall	East	5.25
ES	Windows & Glazed Doors	External Wall	West	1.47
Bathroom	Windows & Glazed Doors	External Wall	West	0.71
Bed 4	Windows & Glazed Doors	External Wall	West	3.36
Bed 3	Windows & Glazed Doors	External Wall	South	3.36
Bed1	Windows & Glazed Doors	External Wall	South	3.36
ES	Windows & Glazed Doors	External Wall	North	1.02
Bed 1	Windows & Glazed Doors	External Wall	North	1.80
Staircase	Windows & Glazed Doors	External Wall	East	1.68
Bed 2	Windows & Glazed Doors	External Wall	East	2.40
14.0 Conservatory	None			
15.0 Draught Proofing	100		%	
16.0 Draught Lobby	No			
17.0 Thermal Bridging	Calculate Bridges			
17.1 List of Bridges				
Bridge Type	Source Type	Length	Psi	Adjusted Reference:
E2 Other lintels (including other steel lintels)	Non Gov Approved Schemes	27.10	0.03	0.03
E3 Sill	Non Gov Approved Schemes	10.54	0.02	0.02
E4 Jamb	Non Gov Approved Schemes	68.40	0.02	0.02
E5 Ground floor (normal)	Non Gov Approved Schemes	45.49	0.05	0.05
E16 Corner (normal)	Non Gov Approved Schemes	40.80	0.04	0.04
E17 Corner (inverted – internal area greater than external area)	Non Gov Approved Schemes	24.00	-0.08	-0.08
E6 Intermediate floor within a dwelling	Non Gov Approved Schemes	43.41	0.00	0.00
E10 Eaves (insulation at ceiling level)	Non Gov Approved Schemes	26.78	0.05	0.05
E13 Gable (insulation at rafter level)	Non Gov Approved Schemes	16.63	0.03	0.03
E14 Flat roof	Non Gov Approved Schemes	4.34	0.04	0.04
Y-value	0.02			W/m ² K
19.0 Mechanical Ventilation				
Mechanical Ventilation				
Mechanical Ventilation System Present	No			
20.0 Fans, Open Fireplaces, Flues				
Number of open chimneys	0			
Number of open flues	0			
Number of chimneys/flues attached to closed fire	0			
Number of flues attached to solid fuel boiler	0			
Number of flues attached to other heater	0			
Number of blocked chimneys	0			
Number of intermittent extract fans	4			
Number of passive vents	0			
Number of flueless gas fires	0			
21.0 Fixed Cooling System	No			
22.0 Pressure Testing	Yes			
Designed AP ₅₀	4.00		m ³ /(h.m ²) @ 50 Pa	
Test Method	Blower Door			
22.0 Lighting				
No Fixed Lighting	No			
	Name Lighting	Efficacy 80.00	Power 5.00	Capacity 400.00
				Count 60
24.0 Main Heating 1	Database			
Percentage of Heat	100.00		%	
Database Ref. No.	103755			
Fuel Type	Electricity			

Summary for Input Data

In Winter	295.11										
In Summer	174.31										
Model Name	aroTHERM 12kW										
Manufacturer	Vaillant Group UK Ltd										
System Type	Heat Pump										
Controls SAP Code	2208										
Is MHS Pumped	Pump in heated space										
Heating Pump Age	2013 or later										
Heat Emitter	Radiators										
Flow Temperature	Enter value										
Flow Temperature Value	45.00										
25.0 Main Heating 2	None										
26.0 Heat Networks	None										
27.0 Secondary Heating	None										
28.0 Water Heating											
Water Heating	Main Heating 1										
SAP Code	901										
Flue Gas Heat Recovery System	No										
Waste Water Heat Recovery Instantaneous System 1	No										
Waste Water Heat Recovery Instantaneous System 2	No										
Waste Water Heat Recovery Storage System	No										
Solar Panel	No										
Water use <= 125 litres/person/day	Yes										
Cold Water Source	From mains										
Bath Count	1										
Immersion Only Heating Hot Water	No										
28.3 Waste Water Heat Recovery System											
29.0 Hot Water Cylinder	Hot Water Cylinder										
Cylinder Stat	Yes										
Cylinder In Heated Space	Yes										
Independent Time Control	Yes										
Insulation Type	Measured Loss										
Cylinder Volume	300.00										
Loss	1.68										
Pipes insulation	All accessible pipework insulated										
In Airing Cupboard	No										
31.0 Thermal Store	None										
34.0 Small-scale Hydro	None										
Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec

Recommendations		Ratings after improvement	
Lower cost measures	None	SAP rating	Environmental Impact
Further measures to achieve even higher standards			
Typical Cost	Typical savings per year	SAP rating	Environmental Impact
£4,000 - £6,000	£103	B 84	A 97
£3,500 - £5,500	£261	B 89	A 98
		0	0