



Centre for Outdoor Sports – Burgess Hill

Schedule of Hard Surfaces

Rev E

10.01.25

Hard Landscaping

Coloured tarmac pedestrian areas including central area to east of pavilion building, sloped approach, footpath adjacent to parent/toddler parking bays NatraTex Cotswold Buff 2.	
Black tarmac pedestrian areas including central area to north and south of pavilion building, footpath to north of car park AC20 dense binder and a 6mm drain asphalt surface course.	
Block paver edging and Features to central area around pavilion building Marshalls Conservation X Block Textured Riven – Colour: Silver Grey Work Dimensions (mm) 240 x 160 x 80	

Head Office Stephen's Yard, Enborne, Newbury, Berkshire RG20 0HA

T 01635 34521

E info@sandcslatter.com

www.sandcslatter.com

A member of The Slatter Group
6537517



VAT Registration No 537 7329 20 Company Registration No

Tactile Paving to Steps Marshalls Tactile Hazard Warning paving 400 x 400 x 50 Colour: Natural Work Dimensions (mm) 398 x 398 x 50	
Steps between Car Park and Central Area Marshalls Conservation X Textured Step 400 x 150 x 1000 Solid unit with textured surface Colour: Silver Grey (not available in Cream) Work Dimensions (mm) 398 x 148 x 1000	
Margin Between Car Park Gabion Wall and 3G Rugby Pitch Fence Permeable and stabilised 20/10 pea-shingle surface (or equivalent)	

Head Office Stephen's Yard, Enborne, Newbury, Berkshire RG20 0HA

T 01635 34521

E info@sandcslatter.com

www.sandcslatter.com

A member of The Slatter Group
6537517



VAT Registration No 537 7329 20 Company Registration No

Paths

Hoggin Footpaths Naturally occurring fine hoggin consisting of sand and gravel, with minimum clay content required to bind the material together, and with no large lumps of clay.	
Green Circle To WSCC Bridleway Standard Details: Supply & lay good quality clean coarse material (suitable for infilling hollows & allowing free drainage beneath the path surface) & create a continuous free draining base for path construction to a 200-300mm depth*, geotextile membrane to base & folded over sides, e.g. Terram 1000 or similar & approved and to a width of 2.0m or as needed. Material grading/size approx. 40mm-200mm no fines. Top Dressing of 100mm depth of Type 1 Limestone or a comparable approved quarried stone compacted and rolled	

Access Road & Car Park

Vehicle Routes Road Spec- AC32 base course with AC20 dense binder and an AC10 SMA surface course.	
--	---

Head Office Stephen’s Yard, Enborne, Newbury, Berkshire RG20 0HA

T 01635 34521

E info@sandcslatter.com

www.sandcslatter.com

A member of The Slatter Group
6537517



VAT Registration No 537 7329 20 Company Registration No

Parking Bays Permeable and stabilised 20/10 pea-shingle surface (or equivalent) Tream Bovpave cellular porous plastic paving grid system	
Drop Down Bollards between Car Park and Sloped Approach to central Area 2no. Broxap Countersunk Fold Down Bollard BX01 5550 Standard Unit Dimensions: Diameter: 89mm, Height: 650mm Colours/Finishes: Jet Black RAL 9005 Refer to 1003 (03) 061_C Coloured Tarmac Location.pdf for location	

Rubbish Bins

Rubbish Bins Located at Top of Steps and Adjacent to Central Area Benches 3no. Broxap Blakemere Litter Bin (45 litre), round, with opened topped design on U-shaped post. Galvanized inner-bin made from wire mesh or sheet metal for easy litter removal. Standard Unit Dimensions: Height: 720mm Diameter: 340mm Capacity: 45 litres Weight: 27kg Colours/Finishes: DB703 Metallic Dark Grey Refer to 1003 (03) 061_C Coloured Tarmac Location.pdf for location	
---	---

Head Office Stephen's Yard, Enborne, Newbury, Berkshire RG20 0HA

T 01635 34521

E info@sandcslatter.com

www.sandcslatter.com

A member of The Slatter Group
6537517



VAT Registration No 537 7329 20 Company Registration No

Outdoor Benches

Central Area Adjacent to Pavilion Building 1 no. Furnitubes Railroad Straight Modules with backrest and Loop in-ground installation support 3230 x 700 mm comprising on one stat and one end unit Wood Finish: Iroko Metal Finish: Anthracite	
Central Area Freestanding 3 no. Furnitubes Railroad Independent Bench with backrest and Loop in-ground installation support 1950 x 700 mm Wood Finish: Iroko Metal Finish: Anthracite Refer to 1003 (03) 061_C Coloured Tarmac Location.pdf for location	
Central Area Circular Seat 1 no. Furnitubes Railroad Curved Modules with Loop in-ground installation support 1250mm radius joined to form circular seat Wood Finish: Iroko Metal Finish: Anthracite Refer to 1003 (03) 061_C Coloured Tarmac Location.pdf for location	
Green Circle Benches Broxap Litchard Seat Heavy duty steel framed seat with seven slats in sturdy timber and a double slatted backrest as standard. Product dimensions: Length: 1800mm, Width: 510mm, Height: 820mm	

Head Office Stephen's Yard, Enborne, Newbury, Berkshire RG20 0HA

T 01635 34521

E info@sandcslatter.com


www.sandcslatter.com

A member of The Slatter Group
6537517



VAT Registration No 537 7329 20 Company Registration No

Gabion Wall

Gabion retaining wall adjacent to car park and gabion wall feature at main entrance and Green Circle entrance Gabion Stone 100/200mm Ragstone quarried rock of irregular shape.	
Gabion retaining wall adjacent to car park and gabion wall feature at main entrance and Green Circle entrance Gabion Basket Gabion baskets, galvanised & welded, 75 x 75mm wire mesh in 0.5m or 1.0m modules to suit locations and use.	

Knee Rail Fence

Knee rail fence between surf pitches and WBLR Lemon Fencing- Full Round Knee Rail Fence (3.6m Length x100mm Diameter)	
--	---

Head Office Stephen’s Yard, Enborne, Newbury, Berkshire RG20 0HA

T 01635 34521

E info@sandcslatter.com

www.sandcslatter.com

A member of The Slatter Group
6537517



VAT Registration No 537 7329 20 Company Registration No