



Air Quality Assessment: 68-70 Keymer Road, Hassocks

December 2023



Experts in air quality
management & assessment

Document Control

Client	Planning Issues Ltd	Principal Contact	Lauren Bishop
---------------	---------------------	--------------------------	---------------

Job Number	J10/15048A/10
-------------------	---------------

Report Prepared By:	Ben Collier & Julia Burnell
----------------------------	-----------------------------

Document Status and Review Schedule

Report No.	Date	Status	Reviewed by
J10/15048A/10/1/F2	4 December 2023	Final	Dr Denise Evans (Associate Director)

This report has been prepared by Air Quality Consultants Ltd on behalf of the Client, taking into account the agreed scope of works. Unless otherwise agreed, this document and all other Intellectual Property Rights remain the property of Air Quality Consultants Ltd.

In preparing this report, Air Quality Consultants Ltd has exercised all reasonable skill and care, taking into account the objectives and the agreed scope of works. Air Quality Consultants Ltd does not accept any liability in negligence for any matters arising outside of the agreed scope of works. The Company operates a Quality Management System, which is certified to ISO 9001:2015, and an Environmental Management System, certified to ISO 14001:2015.

When issued in electronic format, Air Quality Consultants Ltd does not accept any responsibility for any unauthorised changes made by others.

When printed by Air Quality Consultants Ltd, this report will be on Evolve Office, 100% Recycled paper.



Air Quality Consultants Ltd
23 Coldharbour Road, Bristol BS6 7JT Tel: 0117 974 1086
24 Greville Street, Farringdon, London, EC1N 8SS Tel: 020 3873 4780
aqc@aqconsultants.co.uk

Registered Office: 23 Coldharbour Road, Bristol BS6 7JT
Companies House Registration No: 2814570

Executive Summary

The air quality impacts associated with the proposed residential development of 68-70 Keymer Road, Hassocks, have been assessed. This development will consist of 41 retirement apartments, as well as 15 parking spaces.

During the construction works, a range of best practice mitigation measures will be implemented to reduce dust emissions and the overall effect will be 'not significant'; appropriate measures have been set out in this report, to be included in the Dust Management Plan for the works.

Keymer Road is a quiet road and this assessment has demonstrated that all future residents of the proposed development will experience acceptable air quality, with pollutant concentrations below the air quality objectives.

The proposed development will generate additional traffic on the local road network, but the trip generation associated with the proposed development is below published screening criteria. Therefore, the effect of the proposed development on local air quality will be 'not significant'. Furthermore, there will be no significant point sources of emissions within the proposed development as heat and hot water will be provided via all-electric systems.

To encourage the use of more sustainable and less polluting forms of transport, the developer shall commit to providing electric vehicle charging points; 20% of spaces will have active charging and the remaining will provide passive charging abilities.

Overall, the construction and operational air quality effects of the proposed development are judged to be 'not significant'.

Contents

1	Introduction	4
2	Policy Context	6
3	Assessment Criteria	12
4	Assessment Approach	16
5	Baseline Conditions.....	19
6	Construction Phase Impact Assessment	23
7	Operational Phase Impact Assessment.....	28
8	Damage Cost Calculations	30
9	Mitigation.....	32
10	Residual Impacts.....	34
11	Conclusions	35
12	References.....	37
13	Glossary.....	40
14	Appendices	42
A1	Construction Dust Assessment Procedure	43
A2	EPUK & IAQM Planning for Air Quality Guidance.....	50
A3	Professional Experience.....	56
A4	Construction Mitigation.....	57

Tables

Table 1:	Air Quality Criteria for Nitrogen Dioxide, PM ₁₀ and PM _{2.5}	14
Table 2:	Summary of Annual Mean NO ₂ Monitoring (2018-2022) (µg/m ³) ^a	20
Table 3:	Estimated Annual Mean Background Pollutant Concentrations in 2022 and 2026 (µg/m ³)	22
Table 4:	Summary of Soil Characteristics.....	24
Table 5:	Summary of Dust Emission Magnitude.....	25
Table 6:	Summary of the Area Sensitivity	27
Table 7:	Summary of Risk of Impacts Without Mitigation.....	27
Table 8:	Damage Cost Calculation.....	31
Table A1.1:	Examples of How the Dust Emission Magnitude Class May be Defined ...	44
Table A1.2:	Principles to be Used When Defining Receptor Sensitivities.....	46
Table A1.3:	Sensitivity of the Area to Dust Soiling Effects on People and Property	47
Table A1.4:	Sensitivity of the Area to Human Health Effects	48

Table A1.5: Sensitivity of the Area to Ecological Effects	48
Table A1.6: Defining the Risk of Dust Impacts	49
Table A4.1: Best-Practice Mitigation Measures Recommended for the Works.....	57

Figures

Figure 1: Proposed Development Location	4
Figure 2: Monitoring Locations	21
Figure 3: 20 m Distance Band around Site Boundary	25
Figure 4: 20 m Distance Band around Roads Used by Construction Traffic Within 50 m of the Site Exit.....	26

1 Introduction

- 1.1 This report describes the potential air quality impacts associated with the proposed residential development of 68-70 Keymer Road, Hassocks. The proposed development will consist of 41 retirement apartments, as well as 15 parking spaces.
- 1.2 The proposed development is approximately 1 km east of the Air Quality Management Area (AQMA) at the Stonepound Crossroads in Hassocks, declared by Mid Sussex District Council (MSDC) for exceedances of the annual mean nitrogen dioxide (NO₂) objective. The proposed development will lead to changes in vehicle flows on local roads, which may impact on air quality at existing residential properties along the affected road network and thus an assessment is required. The main air pollutants of concern related to road traffic emissions are nitrogen dioxide (NO₂) and fine particulate matter (PM₁₀ and PM_{2.5}).
- 1.3 The location of the proposed development is shown in Figure 1, along with the nearby AQMA.




Figure 1: Proposed Development Location

Contains Ordnance Survey data © Crown copyright and database right 2023. Ordnance Survey licence number 100046099. Additional data sourced from third parties, including public sector information licensed under the Open Government Licence v1.0.

- 1.4 The residential units within the proposed development will be provided with heat and hot water by a combination of electric panel heaters and solar PV; there will be no centralised combustion plant and thus no significant point sources of emissions within the proposed development.
- 1.5 The development design does not currently include any backup-power or emergency-power generators. Should these be added at a later stage, the impacts from the plant emissions may necessitate further assessment.
- 1.6 There is also the potential for the construction activities to impact upon both existing and new properties. The main pollutants of concern related to construction activities are dust and PM₁₀.
- 1.7 This report describes existing local air quality conditions and considers conditions in the future year of 2026, which is the anticipated year of first occupation. The assessment of construction dust impacts focuses on the anticipated duration of the works.
- 1.8 This report has been prepared taking into account all relevant local and national guidance and regulations. Damage cost calculations have been provided in accordance with the Air Quality and Emissions Mitigation Guidance for Sussex document (Sussex Air, 2021).

2 Policy Context

- 2.1 All European legislation referred to in this report is written into UK law and remains in place.

Air Quality Strategy 2007

- 2.2 The Air Quality Strategy (Defra, 2007) published by the Department for Environment, Food, and Rural Affairs (Defra) and Devolved Administrations, provides the policy framework for air quality management and assessment in the UK. It provides air quality standards and objectives for key air pollutants, which are designed to protect human health and the environment. It also sets out how the different sectors: industry, transport and local government, can contribute to achieving the air quality objectives. Local authorities are seen to play a particularly important role. The strategy describes the Local Air Quality Management (LAQM) regime that has been established, whereby every authority has to carry out regular reviews and assessments of air quality in its area to identify whether the objectives have been, or will be, achieved at relevant locations, by the applicable date. If this is not the case, the authority must declare an AQMA, and prepare an action plan which identifies appropriate measures that will be introduced in pursuit of the objectives.

Air Quality Strategy 2023

- 2.3 The Air Quality Strategy: Framework for Local Authority Delivery 2023 (Defra, 2023a) sets out the strategic air quality framework for local authorities and other Air Quality Partners in England. It sets out their powers and responsibilities, and actions the government expects them to take. It does not replace other air quality guidance documents relevant to local authorities.

Clean Air Strategy 2019

- 2.4 The Clean Air Strategy (Defra, 2019) sets out a wide range of actions by which the UK Government will seek to reduce pollutant emissions and improve air quality. Actions are targeted at four main sources of emissions: Transport, Domestic, Farming and Industry. At this stage, there is no straightforward way to take account of the expected future benefits to air quality within this assessment.

Reducing Emissions from Road Transport: Road to Zero Strategy

- 2.5 The Office for Low Emission Vehicles (OLEV) and Department for Transport (DfT) published a Policy Paper (DfT, 2018) in July 2018 outlining how the government will support the transition to zero tailpipe emission road transport and reduce tailpipe emissions from conventional vehicles during the transition. This paper affirms the Government's pledge to end the sale of new conventional petrol and diesel cars and vans by 2040, and states that the Government expects the majority of new cars and vans sold to be 100% zero tailpipe emission and all new cars and vans to have significant zero tailpipe emission capability by this year, and that by 2050 almost every car and van should have

zero tailpipe emissions. It states that the Government wants to see at least 50%, and as many as 70%, of new car sales, and up to 40% of new van sales, being ultra-low emission by 2030.

- 2.6 The paper sets out a number of measures by which Government will support this transition, but is clear that Government expects this transition to be industry and consumer led. The Government has recently announced that 80% of new cars and 70% of new vans sold in Great Britain must be zero emission by 2030, increasing to 100% by 2035. If these ambitions are realised then road traffic-related NO_x emissions can be expected to reduce significantly over the coming decades.

Environment Act 2021

- 2.7 The UK's new legal framework for protection of the natural environment, the Environment Act (2021) passed into UK law in November 2021. The Act gives the Government the power to set long-term, legally binding environmental targets. It also establishes an Office for Environmental Protection (OEP), responsible for holding the government to account and ensuring compliance with these targets.
- 2.8 The Environmental Targets (Fine Particulate Matter) (England) Regulations 2023 (SI 2023 No. 96) sets two new targets for future concentrations of PM_{2.5}. These targets are described in Paragraph 3.5.

Environmental Improvement Plan 2023

- 2.9 Defra published its 25 Year Environment Plan in 2018 (Defra, 2018b). The Environment Act (2021) requires Defra to review this Plan at least every five years. The Environmental Improvement Plan 2023 (Defra, 2023b) is the first revision. This outlines the progress made since 2018 and adds detail to the goals defined in the 2018 Plan, including that of achieving clean air.
- 2.10 The Environmental Improvement Plan 2023 sets out the new air quality targets which have been set for concentrations of PM_{2.5}. These targets, which are described in more detail in Paragraph 3.5, include the long-term targets in the Statutory Instrument described in Paragraph 2.8, and interim targets to be achieved by 2028.
- 2.11 The 2023 Plan outlines the role of local authorities in helping it meet both its targets and existing commitments. It also outlines the respective roles of industry, agricultural sectors, and the Department for Transport in providing the coordinated action required to meet both its new, and pre-existing targets and commitments.

Planning Policy

National Policies

- 2.12 The National Planning Policy Framework (NPPF) (2023) sets out planning policy for England. It states that the purpose of the planning system is to contribute to the achievement of sustainable

development, and that the planning system has three overarching objectives, one of which (Paragraph 8c) is an environmental objective:

“to protect and enhance our natural, built and historic environment; including making effective use of land, improving biodiversity, using natural resources prudently, minimising waste and pollution, and mitigating and adapting to climate change, including moving to a low carbon economy”.

2.13 To prevent unacceptable risks from air pollution, Paragraph 174 of the NPPF states that:

“Planning policies and decisions should contribute to and enhance the natural and local environment by...preventing new and existing development from contributing to, being put at unacceptable risk from, or being adversely affected by unacceptable levels of soil, air, water or noise pollution or land instability. Development should, wherever possible, help to improve local environmental conditions such as air quality”.

2.14 Paragraph 185 states:

“Planning policies and decisions should also ensure that new development is appropriate for its location taking into account the likely effects (including cumulative effects) of pollution on health, living conditions and the natural environment, as well as the potential sensitivity of the site or the wider area to impacts that could arise from the development”.

2.15 More specifically on air quality, Paragraph 186 makes clear that:

“Planning policies and decisions should sustain and contribute towards compliance with relevant limit values or national objectives for pollutants, taking into account the presence of Air Quality Management Areas and Clean Air Zones, and the cumulative impacts from individual sites in local areas. Opportunities to improve air quality or mitigate impacts should be identified, such as through traffic and travel management, and green infrastructure provision and enhancement. So far as possible these opportunities should be considered at the plan-making stage, to ensure a strategic approach and limit the need for issues to be reconsidered when determining individual applications. Planning decisions should ensure that any new development in Air Quality Management Areas and Clean Air Zones is consistent with the local air quality action plan”.

2.16 The NPPF is supported by Planning Practice Guidance (PPG) (Ministry of Housing, Communities & Local Government, 2019), which includes guiding principles on how planning can take account of the impacts of new development on air quality. The PPG states that:

“Defra carries out an annual national assessment of air quality using modelling and monitoring to determine compliance with Limit Values. It is important that the potential impact of new development on air quality is taken into account where the national assessment indicates that relevant limits have been exceeded or are near the limit, or where the need for emissions reductions has been identified”.

2.17 Regarding plan-making, the PPG states:

“It is important to take into account air quality management areas, Clean Air Zones and other areas including sensitive habitats or designated sites of importance for biodiversity where there could be specific requirements or limitations on new development because of air quality”.

- 2.18 The role of the local authorities through the LAQM regime is covered, with the PPG stating that a local authority Air Quality Action Plan *“identifies measures that will be introduced in pursuit of the objectives and can have implications for planning”*. In addition, the PPG makes clear that *“Odour and dust can also be a planning concern, for example, because of the effect on local amenity”*.

- 2.19 Regarding the need for an air quality assessment, the PPG states that:

“Whether air quality is relevant to a planning decision will depend on the proposed development and its location. Concerns could arise if the development is likely to have an adverse effect on air quality in areas where it is already known to be poor, particularly if it could affect the implementation of air quality strategies and action plans and/or breach legal obligations (including those relating to the conservation of habitats and species). Air quality may also be a material consideration if the proposed development would be particularly sensitive to poor air quality in its vicinity”.

- 2.20 The PPG sets out the information that may be required in an air quality assessment, making clear that:

“Assessments need to be proportionate to the nature and scale of development proposed and the potential impacts (taking into account existing air quality conditions), and because of this are likely to be locationally specific”.

- 2.21 The PPG also provides guidance on options for mitigating air quality impacts, as well as examples of the types of measures to be considered. It makes clear that:

“Mitigation options will need to be locationally specific, will depend on the proposed development and need to be proportionate to the likely impact. It is important that local planning authorities work with applicants to consider appropriate mitigation so as to ensure new development is appropriate for its location and unacceptable risks are prevented”.

Local Policies

- 2.22 The Mid Sussex District Plan (Mid Sussex District Council, 2018) was adopted in March 2018 and within this there is one policy which refers to air quality. Policy DP29 states that:

“...The environment, including nationally designated environmental sites, nationally protected landscapes, areas of nature conservation or geological interest, wildlife habitats, and the quality of people’s life will be protected from unacceptable levels of noise, light and air pollution by only permitting development where:

....

Air pollution:

- *It does not cause unacceptable levels of air pollution;*
- *Development on land adjacent to an existing use which generates air pollution or odour would not cause any adverse effects on the proposed development or can be mitigated to reduce exposure to poor air quality to recognised and acceptable levels;*
- *Development proposals (where appropriate) are consistent with Air Quality Management Plans...*

2.23 The Mid Sussex District Plan replaced the Mid Sussex Local Plan (Mid Sussex District Council, 2004) however there are a number of saved policies which remain in place. The main saved policy of relevance is CS22 which states that:

“Development will only be permitted which does not cause unacceptable levels of pollution to land, air or water in terms of noise, dust, fumes, vibration, light or heat. Permissions will not be granted for development on a site adjacent to an existing use which, as a source of pollution, would have an adverse effect on the proposed development.”

2.24 MSDC, as part of the Sussex-air partnership, has produced an Air Quality and Emissions Mitigation Guidance for Sussex document (Sussex Air, 2021), which aims to minimise the impacts new developments may have on local air quality. This guidance has been followed for this assessment.

Building Standards

2.25 Part F(1) of Schedule 1 of the Building Regulations 2010 as amended June 2022 (Ministry of Housing, Communities & Local Government, 2022) places a duty on building owners, or those responsible for relevant building work¹, to ensure adequate ventilation is provided to building occupants.

2.26 Approved Document F (HM Government, 2021a), which accompanies the Building Regulations, explains that care should be taken to minimise entry of external air pollutants. Specific steps should be taken to manage ventilation intakes where the building is near to a significant source of emissions, or if local ambient concentrations exceed values set in the Air Quality Standards Regulations 2010 (see Paragraph 3.10, later). These steps include maximising the distance between emission source and air intake, considering likely dispersion patterns, and considering the timing of pollution releases when designing the ventilation system.

2.27 Part S(1) of Schedule 1, and Regulation 44D, of the Building Regulations 2010 (Ministry of Housing, Communities & Local Government, 2022) define a requirement for the provision of infrastructure for

¹ Building work is a legal term for work covered by the Building Regulations. With limited exemptions, the Regulations apply to all significant building work, including erecting or extending a building.

charging electric vehicles. Precise requirements are explained further within Approved Document S (HM Government, 2021b) and depend on the overall number of parking spaces provided and the average financial cost of installation.

- 2.28 Compliance with the Building Regulations is not required for planning approval, but it is assumed that the Regulations will be complied with in the completed development.

Air Quality Action Plans

National Air Quality Plan

- 2.29 Defra has produced an Air Quality Plan to tackle roadside nitrogen dioxide concentrations in the UK (Defra, 2017); a supplement to the 2017 Plan (Defra, 2018a) was published in October 2018 and sets out the steps Government is taking in relation to a further 33 local authorities where shorter-term exceedances of the limit value were identified. Alongside a package of national measures, the 2017 Plan and the 2018 Supplement require those identified English Local Authorities (or the GLA in the case of London Authorities) to produce local action plans and/or feasibility studies. These plans and feasibility studies must have regard to measures to achieve the statutory limit values within the shortest possible time, which may include the implementation of a Clean Air Zone (CAZ). There is currently no straightforward way to take account of the effects of the 2017 Plan or 2018 Supplement in this assessment; however, consideration has been given to whether there is currently, or is likely to be in the future, a limit value exceedance in the vicinity of the proposed development. This assessment has principally been carried out in relation to the air quality objectives, rather than the limit values that are the focus of the Air Quality Plan.

Local Air Quality Action Plan

- 2.30 MSDC's Air Quality Action Plan (Mid Sussex District Council, 2013) relates to the AQMA at Stonepound Crossroads and sets out a series of measures by which they will seek to achieve the air quality objectives in this AQMA. However, none of the policies are especially relevant to this assessment, being general in nature.

3 Assessment Criteria

- 3.1 The Government has established a set of air quality standards and objectives to protect human health. The 'standards' are set as concentrations below which effects are unlikely even in sensitive population groups, or below which risks to public health would be exceedingly small. They are based purely upon the scientific and medical evidence of the effects of an individual pollutant. The 'objectives' set out the extent to which the Government expects the standards to be achieved by a certain date. They take account of economic efficiency, practicability, technical feasibility and timescale. The objectives for use by local authorities are prescribed within the Air Quality (England) Regulations (2000) and the Air Quality (England) (Amendment) Regulations (2002).
- 3.2 The UK-wide objectives for nitrogen dioxide and PM₁₀ were to have been achieved by 2005 and 2004 respectively, and continue to apply in all future years thereafter. Measurements across the UK have shown that the 1-hour nitrogen dioxide objective is unlikely to be exceeded at roadside locations where the annual mean concentration is below 60 µg/m³ (Defra, 2022). Therefore, 1-hour nitrogen dioxide concentrations will only be considered if the annual mean concentration is above this level. Measurements have also shown that the 24-hour mean PM₁₀ objective could be exceeded at roadside locations where the annual mean concentration is above 32 µg/m³ (Defra, 2022).
- 3.3 The objectives apply at locations where members of the public are likely to be regularly present and are likely to be exposed over the averaging period of the objective. Defra explains where these objectives will apply in its Local Air Quality Management Technical Guidance (Defra, 2022). The annual mean objectives for nitrogen dioxide and PM₁₀ are considered to apply at the façades of residential properties, schools, hospitals etc.; they do not apply at hotels. The 24-hour mean objective for PM₁₀ is considered to apply at the same locations as the annual mean objective, as well as in gardens of residential properties and at hotels. The 1-hour mean objective for nitrogen dioxide applies wherever members of the public might regularly spend 1-hour or more, including outdoor eating locations and pavements of busy shopping streets.
- 3.4 For PM_{2.5}, the objective set by Defra for local authorities is to work toward reducing concentrations without setting any specific numerical value. In the absence of a numerical objective, it is convention to assess local air quality impacts against the limit value (see Paragraph 3.10), originally set at 25 µg/m³ and currently set at 20 µg/m³.
- 3.5 Defra has also recently set two new targets, and two new interim targets, for PM_{2.5} concentrations in England. One set of targets focuses on absolute concentrations. The long-term target is to achieve an annual mean PM_{2.5} concentration of 10 µg/m³ by the end of 2040, with the interim target being a value of 12 µg/m³ by the start of 2028². The second set of targets relate to reducing overall

² Meaning that it will be assessed using measurements from 2027. The 2040 target will be assessed using measurements from 2040. National targets are assessed against concentrations expressed to the nearest whole number, for example a concentration of 10.4 µg/m³ would not exceed the 10 µg/m³ target.

population exposure to PM_{2.5}. By the end of 2040, overall population exposure to PM_{2.5} should be reduced by 35% compared with 2018 levels, with the interim target being a reduction of 22% by the start of 2028.

3.6 Defra will assess compliance with the population exposure targets by averaging concentrations measured at its own background monitoring stations. This will not consider small changes over time to precisely where people are exposed (such as would relate to exposure introduced by a new development). Furthermore, as explained in Paragraph 2.11, all four new targets provide metrics against which central Government can assess its own progress. While local authorities have an important role delivering the required improvements, these are expected to relate to controlling emissions and not to directly assessing PM_{2.5} concentrations against the targets.

3.7 In March 2023, the Department for Levelling Up, Housing and Communities (DLUHC, 2023) explained that the new PM_{2.5} targets will:

“need to be integrated into the planning system, and in setting out planning guidance for local authorities and businesses, we will consider the specific characteristics of PM_{2.5}. The guidance will be forthcoming in due course, until then we expect local authorities to continue to assess local air quality impacts in accordance with existing guidance.”

3.8 Defra has also provided advice (Defra, 2023h) which explains that there is no current requirement to consider the new PM_{2.5} targets in planning decisions and that guidance to local planning authorities will be forthcoming before this position changes. In the future, when planning decisions do need to consider the new targets, the expectation is that this will focus on reducing emissions from new development rather than there being a direct requirement for planning-related air quality assessments to predict PM_{2.5} concentrations.

3.9 For the time being, therefore, no assessment is required, and indeed no robust assessment is possible, in relation to the new PM_{2.5} targets and they are not considered further.

3.10 EU Directive 2008/50/EC (The European Parliament and the Council of the European Union, 2008) sets limit values for nitrogen dioxide, PM₁₀ and PM_{2.5}, and is implemented in UK law through the Air Quality Standards Regulations (2010)³. The limit values for nitrogen dioxide and PM₁₀ are the same numerical concentrations as the UK objectives, but achievement of the limit values is a national obligation rather than a local one and concentrations are reported to the nearest whole number. In the UK, only monitoring and modelling carried out by UK Central Government meets the specification required to assess compliance with the limit values. Central Government does not normally recognise local authority monitoring or local modelling studies when determining the likelihood of the

³ As amended through The Air Quality Standards (Amendment) Regulations 2016 and The Environment (Miscellaneous Amendments) (EU Exit) Regulations 2020.

limit values being exceeded, unless such studies have been audited and approved by Defra and DfT's Joint Air Quality Unit (JAQU).

- 3.11 The relevant air quality criteria for this assessment are provided in Table 1.

Table 1: Air Quality Criteria for Nitrogen Dioxide, PM₁₀ and PM_{2.5}

Pollutant	Time Period	Value
Nitrogen Dioxide	1-hour Mean	200 µg/m ³ not to be exceeded more than 18 times a year
	Annual Mean	40 µg/m ³
PM₁₀	24-hour Mean	50 µg/m ³ not to be exceeded more than 35 times a year
	Annual Mean	40 µg/m ³
PM_{2.5}	Annual Mean	20 µg/m ³ ^a

^a There is no numerical PM_{2.5} objective for local authorities (see Paragraph 3.4). Convention is to assess against the UK limit value which is currently 20 µg/m³.

Construction Dust Criteria

- 3.12 There are no formal assessment criteria for dust. In the absence of formal criteria, the approach developed by the Institute of Air Quality Management (IAQM)⁴ (2016) has been used⁵. Full details of this approach are provided in Appendix A1.

Road Traffic Screening Criteria

- 3.13 Environmental Protection UK (EPUK) and the IAQM recommend a two-stage screening approach (Moorcroft and Barrowcliffe et al, 2017) to determine whether emissions from road traffic generated by a development have the potential for significant air quality impacts. The approach, as described in Appendix A2, first considers the size and parking provision of a development; if the development is residential and is for fewer than ten homes or covers less than 0.5 ha, or is non-residential and will provide less than 1,000 m² of floor space or cover a site area of less than 1 ha, and will provide ten or fewer parking spaces, then there is no need to progress to a detailed assessment.
- 3.14 The second stage then compares the changes in vehicle flows on local roads that a development will lead to against specified screening criteria. The screening thresholds (described in full in Appendix A2) inside an AQMA are a change in flows of more than 25 heavy duty vehicles (HDVs) or 100 light duty vehicles (LDVs) per day; outside of an AQMA the thresholds are 100 HDVs or 500 LDVs. Where these criteria are exceeded, a detailed assessment is likely to be required, although

⁴ The IAQM is the professional body for air quality practitioners in the UK.

⁵ The IAQM issued revised guidance in August 2023, however the guidance includes a number of errors and inconsistencies. A corrected version of the guidance is anticipated shortly, however, to avoid being subject to these errors, this assessment has been based on the 2016 version.

the guidance advises that *“the criteria provided are precautionary and should be treated as indicative”*, and *“it may be appropriate to amend them on the basis of professional judgement”*.

4 Assessment Approach

Existing Conditions

4.1 Existing sources of emissions and baseline air quality conditions within the study area have been defined using a number of approaches:

- industrial and waste management sources that may affect the area have been identified using Defra's Pollutant Release and Transfer Register (Defra, 2023d);
- local sources have been identified through examination of the Council's Air Quality Review and Assessment reports;
- information on existing air quality has been obtained by collating the results of monitoring carried out by the local authority;
- background concentrations have been defined using Defra's 2018-based background maps (Defra, 2023c). These cover the whole of the UK on a 1x1 km grid; and
- whether or not there are any exceedances of the annual mean limit value for nitrogen dioxide in the study area has been identified using the maps of roadside concentrations published by Defra (2020) (2023e). These are the maps used by the UK Government, together with the results from national Automatic Urban and Rural Network (AURN) monitoring sites that operate to the required data quality standards, to identify and report exceedances of the limit value. The national maps of roadside PM₁₀ and PM_{2.5} concentrations (Defra, 2023e), which are available for the years 2009 to 2019, show no exceedances of the limit values anywhere in the UK in 2019.

Construction Impacts

4.2 The construction dust assessment considers the potential for impacts within 350 m of the site boundary, or within 50 m of roads used by construction vehicles. The assessment methodology is that provided by IAQM (2016)⁵. This follows a sequence of steps. Step 1 is a basic screening stage, to determine whether the more detailed assessment provided in Step 2 is required. Step 2a determines the potential for dust to be raised from on-site works and by vehicles leaving the site. Step 2b defines the sensitivity of the area to any dust that may be raised. Step 2c combines the information from Steps 2a and 2b to determine the risk of dust impacts without appropriate mitigation. Step 3 uses this information to determine the appropriate level of mitigation required to ensure that there should be no significant impacts. Appendix A1 explains the approach in more detail.

Road Traffic Impacts

4.3 The first step in considering the road traffic impacts of the proposed development has been to screen the development and its traffic generation against the criteria set out in the EPUK/IAQM guidance

(Moorcroft and Barrowcliffe et al, 2017), as described in Paragraph 3.13 and detailed further in Appendix A2. Where impacts can be screened out there is no need to progress to a more detailed assessment.

Impacts of Road Traffic on Future Residents of the Proposed Development

- 4.4 The impacts of nitrogen dioxide, PM₁₀ and PM_{2.5} concentrations on new residents of the development have been assessed qualitatively, taking account of local air quality monitoring data and proximity to local roads.
- 4.5 The assessment examines air quality conditions in 2022 and assumes these are representative of air quality conditions at the time the development is occupied; this assumption is considered to be worst-case as it is generally expected that nitrogen dioxide, PM₁₀ and PM_{2.5} concentrations will decline in future years.

Assessment of Significance

Construction Dust Significance

- 4.6 Guidance from IAQM (2016) is that, with appropriate mitigation in place, the effects of construction dust will be 'not significant'. The assessment thus focuses on determining the appropriate level of mitigation so as to ensure that effects will normally be 'not significant'.

Operational Significance

- 4.7 There is no official guidance in the UK in relation to development control on how to assess the significance of air quality impacts. The approach developed jointly by Environmental Protection UK (EPUK) and IAQM (Moorcroft and Barrowcliffe et al, 2017) has therefore been used. The overall significance of the air quality impacts is determined using professional judgement; the experience of the consultants preparing the report is set out in Appendix A3. Full details of the EPUK/IAQM approach are provided in Appendix A2.

Damage Cost Calculations

- 4.8 The calculation of damage costs has utilised Defra's Emission Factor Toolkit (EFT) (Defra, 2023c) to determine the development's transport emissions. Defra's damage cost toolkit (Defra, 2023f) has then been used to determine the associated damage costs for those emissions.
- 4.9 The calculation process includes:
- identifying the additional trips that will be generated by the proposed development;
 - calculating the emissions from these trips for the pollutants of concern (NO_x and PM_{2.5}) using the EFT, for each of the five years assessed, starting with the year of opening (2026). This calculation has assumed a 10 km trip length and an average speed of 50 kph in line with the

requirements of the Air Quality and Emissions Mitigation Guidance for Sussex document (Sussex Air, 2021);

- calculating the damage costs for the specific pollutant emissions using the latest damage cost toolkit, based on the costs for Road Transport Urban Medium (DfT, 2023) and a price base year of 2022. The toolkit allows for reductions in emissions over time and applies a health discount rate in line with HM Treasury's Green Book (1.5%); and
- extracting the 'Central' total value for each pollutant and summing these for use as the damage cost total for the scheme.

5 Baseline Conditions

Relevant Features

- 5.1 The proposed development is located approximately 500 m to the east of Hassocks railway station. The application site is bordered by Keymer Road (B2116) to the north. It is currently occupied by residential properties, which occupy the northern half of the site, with associated gardens to the south. There are existing residential properties to the east, west, and south of the site.
- 5.2 The proposed development is located near to an AQMA, as highlighted in Figure 1.

Industrial Sources

- 5.3 No significant industrial or waste management sources have been identified that are likely to affect the proposed development, in terms of air quality.

Local Air Quality Monitoring

- 5.4 MSDC commenced automatic monitoring at a site in East Grinstead in 2022, however this monitor is located over 24 km to the northeast of the proposed development, adjacent to the A22, and is not considered representative of conditions at the proposed development. The Council also operates a number of nitrogen dioxide monitoring sites using diffusion tubes prepared and analysed by Gradko laboratories (using the 20% TEA in water method). The closest of these are located in and around the Stonepound Crossroads AQMA, approximately 1 km to the west of the proposed development. Annual mean results for the years 2018 to 2022 for these sites are summarised in Table 2. Exceedances of the objectives are shown in bold. The monitoring locations are shown in Figure 2. The monitoring data have been taken from Mid Sussex District Council's 2023 Air Quality Annual Status Report (Mid Sussex District Council, 2023).
- 5.5 While 2020 and 2021 results have been presented in this Section for completeness, they are not relied upon in any way as they will not be representative of 'typical' air quality conditions due to the impact of the Covid-19 pandemic on traffic volumes and thus pollutant concentrations.
- 5.6 The annual mean nitrogen dioxide objective was exceeded at two sites within the AQMA in 2018 (MSAQ10 and MSAQ11a/b/c). Concentrations were below the objective at all other sites in all years with concentrations decreasing overall between 2018 and 2022. As measured annual mean nitrogen dioxide concentrations have been well below 60 µg/m³ in all years, it is unlikely that the 1-hour mean nitrogen dioxide objective has been exceeded.

Table 2: Summary of Annual Mean NO₂ Monitoring (2018-2022) (µg/m³)^a

Site No.	Site Type	Location	2018	2019	2020	2021	2022
MSAQ10	Roadside	Traffic Light Keymer Road Hassocks	41.2	39.4	28.4	31.3	30.7
MSAQ11a, MSAQ11b, MSAQ11c	Roadside	Over Court Keymer Road Hassocks	40.1^b	36.3 ^b	27.6 ^b	29.6 ^b	30.4 ^b
MSAQ12	Kerbside	Telegraph Pole Keymer Road Hassocks	33.5	33.9	23.9	25.2	23.7
MSAQ13	Kerbside	Lamp Post Keymer Road Hassocks	38.9	36.6	26.1	30.0	29.1
MSAQ14	Kerbside	Bus Stop London Road Hassocks	34.0	33.5	26.0	26.1	26.9
MSAQ15	Kerbside	Traffic Lights sign London Road Hassocks	35.1	34.0	26.0	27.7	27.8
MSAQ17	Kerbside	Lamp Post Brighton Road Hassocks	28.7	24.3	20.6	22.0	22.5
MSAQ18	Kerbside	Bus Stop Brighton Road Hassocks	28.1	29.3	17.9	21.5	17.4
MSAQ19	Roadside	Lamp Post Hurst Road Hassocks	17.4	15.7	11.9	13.5	12.4
MSAQ23	Roadside	Over Court Eastern Façade Keymer Road Hassocks	34.5	33.4	23.4	24.4	25.7
MSAQ24	Roadside	Over Court Western Façade Keymer Road Hassocks	24.0	22.9	17.8	19.3	18.8
Objective			40				

^a Exceedances of the objectives are shown in bold.^b Average of triplicate diffusion tubes.




Figure 2: Monitoring Locations

Contains Ordnance Survey data © Crown copyright and database right 2023. Ordnance Survey licence number 100046099. Additional data sourced from third parties, including public sector information licensed under the Open Government Licence v1.0.

- 5.7 Monitoring of PM₁₀ concentrations at the automatic monitoring site commenced in 2022. However, the monitoring site is located over 24 km from the proposed development, and data capture for 2022 was less than 40%. Notwithstanding, the measured concentrations were well below the relevant objectives.

Exceedances of Limit Value

- 5.8 There are no AURN (Defra, 2023g) monitoring sites within 1 km of the application site with which to identify exceedances of the annual mean nitrogen dioxide limit value. Defra's roadside annual mean nitrogen dioxide concentrations (Defra, 2023e), which are used to identify and report exceedances of the limit value, do not identify any exceedances within 1 km of the proposed development in 2022. As such, there is considered to be no risk of a limit value exceedance in the vicinity of the proposed development by the time that it is operational.

Background Concentrations

- 5.9 Estimated background concentrations at the proposed development are set out in Table 3 and are all well below the objectives.

Table 3: Estimated Annual Mean Background Pollutant Concentrations in 2022 and 2026 ($\mu\text{g}/\text{m}^3$)

Year	NO ₂	PM ₁₀	PM _{2.5}
2022	8.7	13.4	9.1
2026	7.6	12.9	8.7
Objective	40	40	20 ^a

^a The 20 $\mu\text{g}/\text{m}^3$ PM_{2.5} objective, which was to be met by 2020, is not in Regulations and there is no requirement for local authorities to meet it.

6 Construction Phase Impact Assessment

Construction Traffic

- 6.1 The construction will generate a maximum of two outward heavy goods vehicle (HGV) movements a day. Traffic volumes generated by the site during the construction works will therefore be below the most stringent screening criteria of 25 AADT for heavy vehicles recommended by EPUK/IAQM guidance for inside an AQMA (Moorcroft and Barrowcliffe et al, 2017) and, given the size of the site, it is judged unlikely that light vehicle movements generated during construction would exceed the criteria of 100 AADT.
- 6.2 It is, therefore, not considered necessary to assess the impacts of traffic emissions during the construction phase and it can be concluded that the proposed development will not have a significant impact on local roadside air quality as a result of construction traffic emissions.

On-Site Exhaust Emissions

- 6.3 The IAQM guidance (IAQM, 2016) states:
- “Experience of assessing the exhaust emissions from on-site plant (also known as non-road mobile machinery or NRMM) and site traffic suggests that they are unlikely to make a significant impact on local air quality, and in the vast majority of cases they will not need to be quantitatively assessed. For site plant and on-site traffic, consideration should be given to the number of plant/vehicles and their operating hours and locations to assess whether a significant effect is likely to occur”.*
- 6.4 The proposed development is relatively small, thus the number of NRMM able to operate at any one time will be limited. It is judged that there no risk of significant effects at existing receptors as a result of on-site machinery emissions.

Construction Dust and Particulate Matter Emissions

- 6.5 The construction works will give rise to a risk of dust impacts during demolition, earthworks and construction, as well as from trackout of dust and dirt by vehicles onto the public highway. Step 1 of the assessment procedure is to screen the need for a detailed assessment. There are receptors within the distances set out in the guidance (see Appendix A1), thus a detailed assessment is required. The following section sets out Step 2 of the assessment procedure.

Potential Dust Emission Magnitude

Demolition

- 6.6 There will be a requirement to demolish two existing brick buildings with an approximate total volume of 2,750 m³ and a maximum demolition height of 8.5 m. A mobile crusher may be used on site before removal of the material, but this has not yet been decided; such crushing plant may require a

valid Environmental Permitting Regulations permit. Based on the example definitions set out in Table A1.1 in Appendix A1, the dust emission class for demolition is considered to be *small*.

Earthworks

- 6.7 The characteristics of the soil at the site have been defined using the British Geological Survey's UK Soil Observatory website (British Geological Survey, 2023), as set out in Table 4. Overall, it is considered that, when dry, this soil has the potential to be moderately dusty.

Table 4: Summary of Soil Characteristics

Category	Record
Soil Layer Thickness	Deep-Intermediate
Soil Parent Material Grain Size	Arenaceous ^a
European Soil Bureau Description	Sandstone
Soil Group	Light (Sandy) to Medium (Sandy)
Soil Texture	Sand to Sandy Loam ^b

^a grain size 0.06 – 2.0 mm.

^b a loam is composed mostly of sand and silt.

- 6.8 The site covers approximately 3,500 m² and most of this will be subject to earthworks, involving removal of the foundations of the demolished buildings and breaking up of paved areas. The earthworks will last approximately two months and dust will arise mainly from vehicles travelling over unpaved ground and from the handling of dusty materials (such as dry soil). There will be only one earth-moving vehicle on site at any one time and the total material moved will be less than 100 tonnes. Based on the example definitions set out in Table A1.1 in Appendix A1, the dust emission class for earthworks is considered to be *small*.

Construction

- 6.9 The proposed development involves the construction of a brick building, with a total building volume of approximately 7,200 m³. Dust will arise from vehicles travelling over unpaved ground, the handling and storage of dusty materials, and from the cutting of concrete. The construction will take place over a 61-week period. Based on the example definitions set out in Table A1.1 in Appendix A1, the dust emission class for construction is considered to be *small*.

Trackout


- 6.10 There is expected to be maximum of two outward heavy vehicle movements per day, which may track out dust and dirt, throughout the construction process. Based on the example definitions set out in Table A1.1 in Appendix A1, the dust emission class for trackout is considered to be *small*.
- 6.11 Table 5 summarises the dust emission magnitude for the proposed development.

Table 5: Summary of Dust Emission Magnitude

Source	Dust Emission Magnitude
Demolition	Small
Earthworks	Small
Construction	Small
Trackout	Small

Sensitivity of the Area

- 6.12 This assessment step combines the sensitivity of individual receptors to dust effects with the number of receptors in the area and their proximity to the site. It also considers additional site-specific factors such as topography and screening, and in the case of sensitivity to human health effects, baseline PM₁₀ concentrations.
- 6.13 The IAQM guidance explains that residential properties are 'high' sensitivity receptors to dust soiling (Table A1.2 in Appendix A1). Residential properties are also classified as being of 'high' sensitivity to human health effects, while places of work are classified as being of 'medium' sensitivity. There are approximately seven residential properties within 20 m of the site (see Figure 3).

**Figure 3: 20 m Distance Band around Site Boundary**

Imagery ©2023 Bluesky, Getmapping plc, Infoterra Ltd & Bluesky, Maxar Technologies, Map data ©2023

- 6.14 Table 5 shows that the dust emission magnitude for trackout is *small* and Table A1.3 in Appendix A1 thus explains that there is a risk of material being tracked 50 m from the site exit. Since it is not known which roads construction vehicles will use, it has been assumed that all possible routes could be affected. There are over 10 residential properties within 20 m of the roads along which material could be tracked (see Figure 4).




Figure 4: 20 m Distance Band around Roads Used by Construction Traffic Within 50 m of the Site Exit

Imagery ©2023 Bluesky, Getmapping plc, Infoterra Ltd & Bluesky, Maxar Technologies, Map data ©2023

[Sensitivity of the Area to Effects from Dust Soiling](#)

- 6.15 Using the information set out in Paragraph 6.13 and Figure 3 alongside the matrix set out in Table A1.3 in Appendix A1, the area surrounding the onsite works is of 'medium' sensitivity to dust soiling. Using the information set out in Paragraph 6.14 and Figure 4 alongside the same matrix, the area is of 'high' sensitivity to dust soiling due to trackout.

[Sensitivity of the Area to any Human Health Effects](#)

- 6.16 The matrix in Table A1.4 in Appendix A1 requires information on the baseline annual mean PM₁₀ concentration in the area. The properties nearest the site are set back from local roads and the existing annual mean PM₁₀ concentration is judged to be best described by the background concentration from Table 3 (13.4 µg/m³). Using the information set out in Paragraphs 6.13 and

Figure 3 alongside the matrix in Table A1.4 in Appendix A1, the area surrounding the onsite works is of 'low' sensitivity to human health effects. Using the information set out in Paragraph 6.14 and Figure 4 alongside the same matrix, the area surrounding roads along which material may be tracked from the site is also of 'low' sensitivity.

Sensitivity of the Area to any Ecological Effects

- 6.17 The guidance only considers designated ecological sites within 50 m to have the potential to be impacted by the construction works. There are no designated ecological sites within 50 m of the site boundary or those roads along which material may be tracked, thus ecological impacts will not be considered further.

Summary of the Area Sensitivity

- 6.18 Table 6 summarises the sensitivity of the area around the proposed construction works.

Table 6: Summary of the Area Sensitivity

Effects Associated With:	Sensitivity of the Surrounding Area	
	On-site Works	Trackout
Dust Soiling	Medium Sensitivity	High Sensitivity
Human Health	Low Sensitivity	Low Sensitivity

Risk and Significance

- 6.19 The dust emission magnitudes in Table 5 have been combined with the sensitivities of the area in Table 6 using the matrix in Table A1.6 in Appendix A1, in order to assign a risk category to each activity. The resulting risk categories for the four construction activities, without mitigation, are set out in Table 7. These risk categories have been used to determine the appropriate level of mitigation as set out in Section 9 (step 3 of the assessment procedure).

Table 7: Summary of Risk of Impacts Without Mitigation

Source	Dust Soiling	Human Health
Demolition	Low Risk	Negligible
Earthworks	Low Risk	Negligible
Construction	Low Risk	Negligible
Trackout	Low Risk	Negligible

The IAQM guidance does not provide a method for assessing the significance of effects before mitigation, and advises that pre-mitigation significance should not be determined. With appropriate mitigation in place, the IAQM guidance is clear that the residual effect will normally be 'not significant' (IAQM, 2016).

7 Operational Phase Impact Assessment

Impacts at Existing Receptors

Assessment of Development-Generated Road Traffic Emissions

- 7.1 The proposed development is expected to generate an additional 60 light duty vehicles trips per day on the local road network, of which 66% would travel west and 34% would travel east; this trip rate is below the most stringent screening threshold of 100 LDVs recommended for use inside of an AQMA in the EPUK/IAQM guidance (Moorcroft and Barrowcliffe et al, 2017) (see Paragraph 3.14). The proposed development will not generate any heavy vehicle trips.
- 7.2 As such, it is judged that the relevant screening thresholds will not be exceeded and there is no requirement for a detailed assessment of road traffic impacts at existing receptors; it can be concluded that the proposed development will not have a significant impact on local roadside air quality.

Impacts of Existing Sources on Future Residents of the Development

- 7.3 The proposed development is located on Keymer Road, outside the Stonepound Crossroads AQMA. Therefore, the roadside concentrations measured at monitoring sites MSAQ12 and MSAQ13 (as presented in Table 2) are considered most representative of conditions at the proposed development site as these are also located on Keymer Road, outside the AQMA. However, the façade of the proposed development is set back from Keymer Road by at least 15 m and therefore the concentrations at the proposed development site are expected to be lower than those recorded at these monitors (which are within 2 m of the kerbside). Given that between 2018 and 2022, there have been no exceedances of the annual mean nitrogen dioxide objective at MSAQ12 and MSAQ13, the concentrations at the proposed development would also be expected to be below the objective. As concentrations at these sites are also well below 60 µg/m³, this indicates there is unlikely to be exceedances of the hourly mean nitrogen dioxide objective at the proposed development.
- 7.4 Areas towards the middle and rear of the site (more than 50 m from Keymer Road) are expected to experience concentrations close to background levels, as presented in Table 3. As estimated NO₂, PM₁₀, and PM_{2.5} background concentrations at the site are also well below the objectives, it can be concluded that future residents will experience acceptable air quality, and there is no need for more detailed assessment.

Significance of Operational Air Quality Effects

- 7.5 The operational air quality effects without mitigation are judged to be 'not significant'. This professional judgement is made in accordance with the methodology set out in Appendix A2, and takes account of the assessment that:

- pollutant concentrations within the proposed development will all be below the objectives, thus future residents will experience acceptable air quality; and
- the proposed development will generate traffic well below industry screening thresholds.

8 Damage Cost Calculations

Background

- 8.1 Defra developed the damage cost approach to enable proportionate analysis when assessing relatively small impacts on air quality. The damage costs are a set of impact values which were derived using the more detailed Impact Pathway Approach. These values estimate the societal costs associated with small changes in pollutant emissions. Combined with emission change estimates, they provide an approximate valuation of the aggregate societal impacts of a policy. Such impacts can then be set against the direct monetary costs of a scheme to provide a cost-benefit calculation. Thus, damage costs do not provide a figure for the abatement of emissions to a given level.
- 8.2 Abatement costs are usually derived from a marginal abatement cost curve (MACC) which gives the incremental cost of measures to achieve a certain outcome, such as the removal of an exceedance of the air quality objectives. However, the measures available and their associated costs are quite time-specific which means that they need to be updated on a regular basis. Defra's last MACC for NO₂ exceedances was produced several years ago and has now been withdrawn. There are therefore no Defra approved abatement costs for air quality currently available. Thus, while damage costs are not the same as abatement costs, they provide a current and available resource for assigning value to air pollution emissions.

Calculations

- 8.3 Paul Basham Associates, who have undertaken the Transport Assessment for the proposed development, have advised that the development will generate 60 additional vehicle trips per day, on average, on the local road network, all of which will be light duty vehicles. The annual emissions from each of these trips in the five years from the year of opening have been calculated using the EFT and entered into Defra's damage cost toolkit. The calculations and results are presented in Table 8.

Table 8: Damage Cost Calculation

Year	2026	2027	2028	2029	2030
NOx					
Total Emissions (tonnes)	0.0333	0.0298	0.0267	0.0241	0.0219
Central Damage Cost (£) ^a	9,054	9,054	9,054	9,054	9,054
Discounted Central Cost (£)	301	266	235	209	186
Total Central Present Value (£)	£1,197				
PM _{2.5}					
Total Emissions (tonnes)	0.00380	0.00379	0.00378	0.00377	0.00376
Central Damage Cost (£) ^a	63,766	63,766	63,766	63,766	63,766
Discounted Central Cost (£)	242	238	234	230	226
Total Central Present Value (£)	£1,170				

^a Road transport urban medium

8.4 Summing the values for NO_x and PM_{2.5} gives a total damage cost of **£2,367**.

9 Mitigation

Good Design and Best Practice

- 9.1 The EPUK/IAQM guidance advises that good design and best practice measures should be considered, whether or not more specific mitigation is required.
- 9.2 The proposed development incorporates the following good design and best practice measures:
- setting back of the development buildings from roads by at least 15 m; and
 - provision of active electric vehicle charging facilities for 20% of spaces, with passive provision for all remaining spaces, as required by Principle B of the West Sussex County Council Guidance on Parking at New Developments (West Sussex County Council, 2020).

Recommended Mitigation Measures

Construction Impacts

- 9.3 Measures to mitigate dust emissions will be required during the construction phase of the development in order to minimise effects upon nearby sensitive receptors.
- 9.4 The site has been identified as a *Low Risk* site during demolition, earthworks, construction, and for trackout, as set out in Table 7. Comprehensive guidance has been published by IAQM (2016) that describes measures that should be employed, as appropriate, to reduce the impacts, along with guidance on monitoring during demolition and construction (IAQM, 2018). This reflects best practice experience and has been used, together with the professional experience of the consultant who has undertaken the dust impact assessment and the findings of the assessment, to draw up a set of measures that should be incorporated into the specification for the works. These measures are described in Appendix A4.
- 9.5 Where mitigation measures rely on water, it is expected that only sufficient water will be applied to damp down the material. There should not be any excess to potentially contaminate local watercourses.

Road Traffic Impacts

- 9.6 The assessment has demonstrated that the overall air quality effect of the proposed development will be 'not significant'; it will not introduce any new exposure into areas of unacceptable air quality, nor will the development-generated traffic emissions have a significant impact on local air quality. It is, therefore, not considered appropriate to propose further mitigation measures for this development.

- 9.7 Measures to reduce pollutant emissions from road traffic are principally being delivered in the longer term by the introduction of more stringent emissions standards, largely via European legislation (which is written into UK law).
- 9.8 The proposed development is, however, required to demonstrate the implementation of mitigation measures to improve air quality and reduce emissions, totalling at least £2,367 (Table 8). It is anticipated that the costs for the proposed EV charging points will be greater than the damage mitigation costs calculated.

10 Residual Impacts

Construction

- 10.1 The IAQM guidance is clear that, with appropriate mitigation in place, the residual effects will normally be 'not significant'. The mitigation measures set out in Section 9 and Appendix A4 are based on the IAQM guidance. With these measures in place and effectively implemented the residual effects are judged to be 'not significant'.
- 10.2 The IAQM guidance does, however, recognise that, even with a rigorous dust management plan in place, it is not possible to guarantee that the dust mitigation measures will be effective all of the time, for instance under adverse weather conditions. During these events, short-term dust annoyance may occur, however, the scale of this would not normally be considered sufficient to change the conclusion that overall the effects will be 'not significant'.

Road Traffic Impacts

- 10.3 The residual impacts will be the same as those identified in Section 7. The overall effects of the proposed development will be 'not significant'.

11 Conclusions

- 11.1 The assessment has considered the impacts of the proposed development on local air quality in terms of dust and particulate matter emissions during construction and emissions from road traffic generated by the completed and occupied development. It has also identified the air quality conditions that future residents will experience. Damage cost calculations have been carried out in accordance with the Air Quality and Emissions Mitigation Guidance for Sussex document.

Construction Impacts

- 11.2 The construction works have the potential to create dust. During construction it will therefore be necessary to apply a package of mitigation measures to minimise dust emissions. Appropriate measures have been recommended and, with these measures in place, it is expected that any residual effects will be 'not significant'.

Operational Impacts

- 11.3 The assessment has demonstrated that the changes to traffic flows on the local road network are below the EPUK/IAQM screening thresholds, and therefore that the effects of road traffic on local air quality will be not significant.
- 11.4 Air quality conditions for future residents of the proposed development have been shown to be acceptable, with concentrations below the air quality objectives throughout the site.
- 11.5 The overall operational air quality effects of the proposed development are therefore judged to be 'not significant'.

Damage Cost Calculations

- 11.6 Damage cost calculations for NO_x and PM_{2.5}, carried out in accordance with MSDC's Air Quality and Emissions Guidance Document, give a total damage cost of **£2,367**. It should be noted that the damage cost approach was not developed to provide a figure for the abatement of emissions to a given level (see Paragraphs 8.1 and 8.2).

Policy Implications

- 11.7 Taking into account these conclusions, it is judged that the proposed development is consistent with Paragraph 185 of the NPPF, being appropriate for its location both in terms of its effects on the local air quality environment and the air quality conditions for future residents. It is also consistent with Paragraph 186, as it will not affect compliance with relevant limit values or national objectives.

- 11.8 The proposed development is also consistent with Policy DP29 of MSDC's District Plan and saved policy CS22 of the Local Plan, as it will not have an unacceptable impact on air quality, and existing sources will not have an adverse effect on the proposed development itself.

12 References

- British Geological Survey (2023) *UK Soil Observatory Map Viewer*, Available: <http://mapapps2.bgs.ac.uk/ukso/home.html>.
- Defra (2007) *The Air Quality Strategy for England, Scotland, Wales and Northern Ireland*, Defra.
- Defra (2017) *Air quality plan for nitrogen dioxide (NO₂) in the UK*, Available: <https://www.gov.uk/government/publications/air-quality-plan-for-nitrogen-dioxide-no2-in-uk-2017>.
- Defra (2018a) *Supplement to the UK plan for tackling roadside nitrogen dioxide concentrations*, Available: https://assets.publishing.service.gov.uk/government/uploads/system/uploads/attachment_data/file/746100/air-quality-no2-plan-supplement.pdf.
- Defra (2018b) *A Green Future: Our 25 Year Plan to Improve the Environment*, [Online], Available: https://assets.publishing.service.gov.uk/government/uploads/system/uploads/attachment_data/file/693158/25-year-environment-plan.pdf.
- Defra (2019) *Clean Air Strategy 2019*, Available: <https://www.gov.uk/government/publications/clean-air-strategy-2019>.
- Defra (2020) *2020 NO₂ projections data (2018 reference year)*, Available: <https://uk-air.defra.gov.uk/library/no2ten/2020-no2-pm-projections-from-2018-data>.
- Defra (2022) *Review & Assessment: Technical Guidance LAQM.TG22 August 2022 Version*, [Online], Available: <https://laqm.defra.gov.uk/wp-content/uploads/2022/08/LAQM-TG22-August-22-v1.0.pdf>.
- Defra (2023a) *Air Quality Strategy: Framework for Local Authority Delivery*, [Online], Available: <https://www.gov.uk/government/publications/the-air-quality-strategy-for-england/air-quality-strategy-framework-for-local-authority-delivery>.
- Defra (2023b) *Environmental Improvement Plan 2023*, [Online], Available: https://assets.publishing.service.gov.uk/government/uploads/system/uploads/attachment_data/file/1133967/environmental-improvement-plan-2023.pdf.
- Defra (2023c) *Local Air Quality Management (LAQM) Support Website*, Available: <http://laqm.defra.gov.uk/>.
- Defra (2023d) *UK Pollutant Release and Transfer Register*, Available: <http://prtr.defra.gov.uk/map-search>.
- Defra (2023e) *UK Ambient Air Quality Interactive Map*, Available: <https://uk-air.defra.gov.uk/data/gis-mapping>.
- Defra (2023f) *Damage Cost Guidance and Toolkit*, Available: <https://www.gov.uk/government/publications/assess-the-impact-of-air-quality/air-quality-appraisal-damage-cost-guidance>.

- Defra (2023g) *Defra AURN Archive*, Available: <https://uk-air.defra.gov.uk/interactive-map?network=aurn>.
- Defra (2023h) 'Integrating the Environment Act air quality targets into the planning system'.
- Department for Levelling Up, Housing and Communities (DLUHC) (2023) *National Planning Policy Framework*, [Online], Available: https://assets.publishing.service.gov.uk/government/uploads/system/uploads/attachment_data/file/1182995/NPPF_Sept_23.pdf.
- DfT (2018) *The Road to Zero: Next steps towards cleaner road transport and delivering our Industrial Strategy*.
- DfT (2023) *TAG Unit A5.4 Marginal External Costs*.
- DLUHC (2023) 'Planning Newsletter'.
- Environment Act 2021 (2021).
- HM Government (2021a) *Ventilation - Approved Document F*, [Online], Available: <https://www.gov.uk/government/publications/ventilation-approved-document-f>.
- HM Government (2021b) *Infrastructure for the charging of electric vehicles - Approved Document S*, [Online], Available: https://assets.publishing.service.gov.uk/government/uploads/system/uploads/attachment_data/file/1057375/AD_S.pdf.
- IAQM (2016) *Guidance on the Assessment of Dust from Demolition and Construction v1.1*, Available: <http://iaqm.co.uk/guidance/>.
- IAQM (2018) *Guidance on Air Quality Monitoring in the Vicinity of Demolition and Construction Sites v1.1*, Available: www.iaqm.co.uk/guidance.html.
- Mid Sussex District Council (2004) *Mid Sussex Local Plan*.
- Mid Sussex District Council (2013) *Air Quality Action Plan Stonepound Crossroad, Hassocks*.
- Mid Sussex District Council (2018) *Mid Sussex District Plan 2014 - 2031*.
- Mid Sussex District Council (2023) *2023 Air Quality Annual Status Report (ASR)*.
- Ministry of Housing, Communities & Local Government (2019) *Planning Practice Guidance*, Available: <https://www.gov.uk/government/collections/planning-practice-guidance>.
- Ministry of Housing, Communities & Local Government (2022) *The Building Regulations 2010 Schedule 1*, 201022141st edition, Available: https://assets.publishing.service.gov.uk/government/uploads/system/uploads/attachment_data/file/899279/Single_stitched_together_pdf_of_all_ADs__Jun20_.pdf.
- Moorcroft and Barrowcliffe et al (2017) *Land-Use Planning & Development Control: Planning For Air Quality v1.2*, IAQM, London, Available: <http://iaqm.co.uk/guidance/>.
- Sussex Air (2021) *Air Quality and Emissions Mitigation Guidance for Sussex*.

The Air Quality (England) (Amendment) Regulations 2002, Statutory Instrument 3043 (2002), HMSO, Available: <https://www.legislation.gov.uk/uksi/2002/3043/contents/made>.

The Air Quality (England) Regulations 2000 Statutory Instrument 928 (2000), HMSO, Available: <http://www.legislation.gov.uk/uksi/2000/928/contents/made>.

The Air Quality Standards Regulations 2010 Statutory Instrument 1001 (2010), HMSO, Available: http://www.legislation.gov.uk/uksi/2010/1001/pdfs/uksi_20101001_en.pdf.

The European Parliament and the Council of the European Union (2008) *Directive 2008/50/EC of the European Parliament and of the Council*, Available: <http://eur-lex.europa.eu/legal-content/EN/TXT/?uri=celex%3A32008L0050>.

West Sussex County Council (2020) *West Sussex County Council Guidance on Parking at New Developments*.

13 Glossary

AADT	Annual Average Daily Traffic
AQC	Air Quality Consultants
AQMA	Air Quality Management Area
AURN	Automatic Urban and Rural Network
Defra	Department for Environment, Food and Rural Affairs
DMP	Dust Management Plan
EFT	Emission Factor Toolkit
EPUK	Environmental Protection UK
EU	European Union
EV	Electric Vehicle
Exceedance	A period of time when the concentration of a pollutant is greater than the appropriate air quality objective. This applies to specified locations with relevant
HDV	Heavy Duty Vehicles (> 3.5 tonnes)
HMSO	Her Majesty's Stationery Office
IAQM	Institute of Air Quality Management
JAQU	Joint Air Quality Unit
kph	Kilometres Per hour
LAQM	Local Air Quality Management
LDV	Light Duty Vehicles (<3.5 tonnes)
LGV	Light Goods Vehicle
µg/m³	Microgrammes per cubic metre
MACC	Marginal Abatement Cost Curve
NO	Nitric oxide
NO₂	Nitrogen dioxide
NO_x	Nitrogen oxides (taken to be NO ₂ + NO)
NPPF	National Planning Policy Framework
OEP	Office for Environmental Protection

Objectives	A nationally defined set of health-based concentrations for nine pollutants, seven of which are incorporated in Regulations, setting out the extent to which the standards should be achieved by a defined date. There are also vegetation-based objectives for sulphur dioxide and nitrogen oxides
OLEV	Office for Low Emission Vehicles
PM₁₀	Small airborne particles, more specifically particulate matter less than 10 micrometres in aerodynamic diameter
PM_{2.5}	Small airborne particles less than 2.5 micrometres in aerodynamic diameter
PPG	Planning Practice Guidance
SPD	Supplementary Planning Document
Standards	A nationally defined set of concentrations for nine pollutants below which health effects do not occur or are minimal
TEA	Triethanolamine – used to absorb nitrogen dioxide

14 Appendices

A1	Construction Dust Assessment Procedure	43
A2	EPUK & IAQM Planning for Air Quality Guidance.....	50
A3	Professional Experience.....	56
A4	Construction Mitigation.....	57

A1 Construction Dust Assessment Procedure

A1.1 The criteria developed by IAQM (2016) divide the activities on construction sites into four types to reflect their different potential impacts. These are:

- demolition;
- earthworks;
- construction; and
- trackout.

A1.2 The assessment procedure includes the four steps summarised below:

STEP 1: Screen the Need for a Detailed Assessment

A1.3 An assessment is required where there is a human receptor within 350 m of the boundary of the site and/or within 50 m of the route(s) used by construction vehicles on the public highway, up to 500 m from the site entrance(s), or where there is an ecological receptor within 50 m of the boundary of the site and/or within 50 m of the route(s) used by construction vehicles on the public highway, up to 500 m from the site entrance(s).

A1.4 Where the need for a more detailed assessment is screened out, it can be concluded that the level of risk is *negligible* and that any effects will be 'not significant'. No mitigation measures beyond those required by legislation will be required.

STEP 2: Assess the Risk of Dust Impacts

A1.5 A site is allocated to a risk category based on two factors:

- the scale and nature of the works, which determines the potential dust emission magnitude (Step 2A); and
- the sensitivity of the area to dust effects (Step 2B).

A1.6 These two factors are combined in Step 2C, which is to determine the risk of dust impacts with no mitigation applied. The risk categories assigned to the site may be different for each of the four potential sources of dust (demolition, earthworks, construction and trackout).

Step 2A – Define the Potential Dust Emission Magnitude

A1.7 Dust emission magnitude is defined as either 'Small', 'Medium', or 'Large'. The IAQM guidance explains that this classification should be based on professional judgement, but provides the examples in Table A1.1.

Table A1.1: Examples of How the Dust Emission Magnitude Class May be Defined

Class	Examples
Demolition	
Large	Total building volume >50,000 m ³ , potentially dusty construction material (e.g. concrete), on site crushing and screening, demolition activities >20 m above ground level
Medium	Total building volume 20,000 m ³ – 50,000 m ³ , potentially dusty construction material, demolition activities 10-20 m above ground level
Small	Total building volume <20,000 m ³ , construction material with low potential for dust release (e.g. metal cladding or timber), demolition activities <10 m above ground, demolition during wetter months
Earthworks	
Large	Total site area >10,000 m ² , potentially dusty soil type (e.g. clay, which will be prone to suspension when dry to due small particle size), >10 heavy earth moving vehicles active at any one time, formation of bunds >8 m in height, total material moved >100,000 tonnes
Medium	Total site area 2,500 m ² – 10,000 m ² , moderately dusty soil type (e.g. silt), 5-10 heavy earth moving vehicles active at any one time, formation of bunds 4 m – 8 m in height, total material moved 20,000 tonnes – 100,000 tonnes
Small	Total site area <2,500 m ² , soil type with large grain size (e.g. sand), <5 heavy earth moving vehicles active at any one time, formation of bunds <4 m in height, total material moved <20,000 tonnes, earthworks during wetter months
Construction	
Large	Total building volume >100,000 m ³ , piling, on site concrete batching; sandblasting
Medium	Total building volume 25,000 m ³ – 100,000 m ³ , potentially dusty construction material (e.g. concrete), piling, on site concrete batching
Small	Total building volume <25,000 m ³ , construction material with low potential for dust release (e.g. metal cladding or timber)
Trackout ^a	
Large	>50 HDV (>3.5t) outward movements in any one day, potentially dusty surface material (e.g. high clay content), unpaved road length >100 m
Medium	10-50 HDV (>3.5t) outward movements in any one day, moderately dusty surface material (e.g. high clay content), unpaved road length 50 m – 100 m
Small	<10 HDV (>3.5t) outward movements in any one day, surface material with low potential for dust release, unpaved road length <50 m

^a These numbers are for vehicles that leave the site after moving over unpaved ground.

Step 2B – Define the Sensitivity of the Area

A1.8 The sensitivity of the area is defined taking account of a number of factors:

- the specific sensitivities of receptors in the area;
- the proximity and number of those receptors;
- in the case of PM₁₀, the local background concentration; and
- site-specific factors, such as whether there are natural shelters to reduce the risk of wind-blown dust.

- A1.9 The first requirement is to determine the specific sensitivities of local receptors. The IAQM guidance recommends that this should be based on professional judgment, taking account of the principles in Table A1.2. These receptor sensitivities are then used in the matrices set out in Table A1.3, Table A1.4 and Table A1.5 to determine the sensitivity of the area. Finally, the sensitivity of the area is considered in relation to any other site-specific factors, such as the presence of natural shelters etc., and any required adjustments to the defined sensitivities are made.

Step 2C – Define the Risk of Impacts

- A1.10 The dust emission magnitude determined at Step 2A is combined with the sensitivity of the area determined at Step 2B to determine the *risk* of impacts with no mitigation applied. The IAQM guidance provides the matrix in Table A1.6 as a method of assigning the level of risk for each activity.

STEP 3: Determine Site-specific Mitigation Requirements

- A1.11 The IAQM guidance provides a suite of recommended and desirable mitigation measures which are organised according to whether the outcome of Step 2 indicates a low, medium, or high risk. The list provided in the IAQM guidance has been used as the basis for the requirements set out in Appendix A4.

STEP 4: Determine Significant Effects

- A1.12 The IAQM guidance does not provide a method for assessing the significance of effects before mitigation, and advises that pre-mitigation significance should not be determined. With appropriate mitigation in place, the IAQM guidance is clear that the residual effect will normally be 'not significant'.
- A1.13 The IAQM guidance recognises that, even with a rigorous dust management plan in place, it is not possible to guarantee that the dust mitigation measures will be effective all of the time, for instance under adverse weather conditions. The local community may therefore experience occasional, short-term dust annoyance. The scale of this would not normally be considered sufficient to change the conclusion that the effects will be 'not significant'.

Table A1.2: Principles to be Used When Defining Receptor Sensitivities

Class	Principles	Examples
Sensitivities of People to Dust Soiling Effects		
High	users can reasonably expect enjoyment of a high level of amenity; or the appearance, aesthetics or value of their property would be diminished by soiling; and the people or property would reasonably be expected to be present continuously, or at least regularly for extended periods, as part of the normal pattern of use of the land	dwellings, museum and other culturally important collections, medium and long term car parks and car showrooms
Medium	users would expect to enjoy a reasonable level of amenity, but would not reasonably expect to enjoy the same level of amenity as in their home; or the appearance, aesthetics or value of their property could be diminished by soiling; or the people or property wouldn't reasonably be expected to be present here continuously or regularly for extended periods as part of the normal pattern of use of the land	parks and places of work
Low	the enjoyment of amenity would not reasonably be expected; or there is property that would not reasonably be expected to be diminished in appearance, aesthetics or value by soiling; or there is transient exposure, where the people or property would reasonably be expected to be present only for limited periods of time as part of the normal pattern of use of the land	playing fields, farmland (unless commercially-sensitive horticultural), footpaths, short term car parks and roads
Sensitivities of People to the Health Effects of PM₁₀		
High	locations where members of the public may be exposed for eight hours or more in a day	residential properties, hospitals, schools and residential care homes
Medium	locations where the people exposed are workers, and where individuals may be exposed for eight hours or more in a day.	may include office and shop workers, but will generally not include workers occupationally exposed to PM ₁₀
Low	locations where human exposure is transient	public footpaths, playing fields, parks and shopping streets
Sensitivities of Receptors to Ecological Effects		
High	locations with an international or national designation and the designated features may be affected by dust soiling; or locations where there is a community of a particularly dust sensitive species	Special Areas of Conservation with dust sensitive features
Medium	locations where there is a particularly important plant species, where its dust sensitivity is uncertain or unknown; or locations with a national designation where the features may be affected by dust deposition	Sites of Special Scientific Interest with dust sensitive features
Low	locations with a local designation where the features may be affected by dust deposition	Local Nature Reserves with dust sensitive features

Table A1.3: Sensitivity of the Area to Dust Soiling Effects on People and Property ⁶

Receptor Sensitivity	Number of Receptors	Distance from the Source (m)			
		<20	<50	<100	<350
High	>100	High	High	Medium	Low
	10-100	High	Medium	Low	Low
	1-10	Medium	Low	Low	Low
Medium	>1	Medium	Low	Low	Low
Low	>1	Low	Low	Low	Low

⁶ For demolition, earthworks and construction, distances are taken either from the dust source or from the boundary of the site. For trackout, distances are measured from the sides of roads used by construction traffic. Without mitigation, trackout may occur from roads up to 500 m from sites with a *large* dust emission magnitude for trackout, 200 m from sites with a *medium* dust emission magnitude and 50 m from sites with a *small* dust emission magnitude, as measured from the site exit. The impact declines with distance from the site, and it is only necessary to consider trackout impacts up to 50 m from the edge of the road.

Table A1.4: Sensitivity of the Area to Human Health Effects ⁶

Receptor Sensitivity	Annual Mean PM ₁₀	Number of Receptors	Distance from the Source (m)				
			<20	<50	<100	<200	<350
High	>32 µg/m ³	>100	High	High	High	Medium	Low
		10-100	High	High	Medium	Low	Low
		1-10	High	Medium	Low	Low	Low
	28-32 µg/m ³	>100	High	High	Medium	Low	Low
		10-100	High	Medium	Low	Low	Low
		1-10	High	Medium	Low	Low	Low
	24-28 µg/m ³	>100	High	Medium	Low	Low	Low
		10-100	High	Medium	Low	Low	Low
		1-10	Medium	Low	Low	Low	Low
	<24 µg/m ³	>100	Medium	Low	Low	Low	Low
		10-100	Low	Low	Low	Low	Low
		1-10	Low	Low	Low	Low	Low
Medium	>32 µg/m ³	>10	High	Medium	Low	Low	Low
		1-10	Medium	Low	Low	Low	Low
	28-32 µg/m ³	>10	Medium	Low	Low	Low	Low
		1-10	Low	Low	Low	Low	Low
	24-28 µg/m ³	>10	Low	Low	Low	Low	Low
		1-10	Low	Low	Low	Low	Low
	<24 µg/m ³	>10	Low	Low	Low	Low	Low
		1-10	Low	Low	Low	Low	Low
Low	-	>1	Low	Low	Low	Low	Low

Table A1.5: Sensitivity of the Area to Ecological Effects ⁶

Receptor Sensitivity	Distance from the Source (m)	
	<20	<50
High	High	Medium
Medium	Medium	Low
Low	Low	Low

Table A1.6: Defining the Risk of Dust Impacts

Sensitivity of the Area	Dust Emission Magnitude		
	Large	Medium	Small
Demolition			
High	High Risk	Medium Risk	Medium Risk
Medium	High Risk	Medium Risk	Low Risk
Low	Medium Risk	Low Risk	Negligible
Earthworks			
High	High Risk	Medium Risk	Low Risk
Medium	Medium Risk	Medium Risk	Low Risk
Low	Low Risk	Low Risk	Negligible
Construction			
High	High Risk	Medium Risk	Low Risk
Medium	Medium Risk	Medium Risk	Low Risk
Low	Low Risk	Low Risk	Negligible
Trackout			
High	High Risk	Medium Risk	Low Risk
Medium	Medium Risk	Low Risk	Negligible
Low	Low Risk	Low Risk	Negligible

A2 EPUK & IAQM Planning for Air Quality Guidance

- A2.1 The guidance issued by EPUK and IAQM (Moorcroft and Barrowcliffe et al, 2017) is comprehensive in its explanation of the place of air quality in the planning regime. Key sections of the guidance not already mentioned above are set out below.

Air Quality as a Material Consideration

“Any air quality issue that relates to land use and its development is capable of being a material planning consideration. The weight, however, given to air quality in making a planning application decision, in addition to the policies in the local plan, will depend on such factors as:

- *the severity of the impacts on air quality;*
- *the air quality in the area surrounding the proposed development;*
- *the likely use of the development, i.e. the length of time people are likely to be exposed at that location; and*
- *the positive benefits provided through other material considerations”.*

Recommended Best Practice

- A2.2 The guidance goes into detail on how all development proposals can and should adopt good design principles that reduce emissions and contribute to better air quality management. It states:

“The basic concept is that good practice to reduce emissions and exposure is incorporated into all developments at the outset, at a scale commensurate with the emissions”.

- A2.3 The guidance sets out a number of good practice principles that should be applied to all developments that:

- include 10 or more dwellings;
- where the number of dwellings is not known, residential development is carried out on a site of more than 0.5 ha;
- provide more than 1,000 m² of commercial floorspace;
- are carried out on land of 1 ha or more.

- A2.4 The good practice principles are that:

- New developments should not contravene the Council's Air Quality Action Plan, or render any of the measures unworkable;
- Wherever possible, new developments should not create a new “street canyon”, as this inhibits pollution dispersion;

- Delivering sustainable development should be the key theme of any application;
- New development should be designed to minimise public exposure to pollution sources, e.g. by locating habitable rooms away from busy roads;
- The provision of at least 1 Electric Vehicle (EV) “rapid charge” point per 10 residential dwellings and/or 1000 m² of commercial floorspace. Where on-site parking is provided for residential dwellings, EV charging points for each parking space should be made available;
- Where development generates significant additional traffic, provision of a detailed travel plan (with provision to measure its implementation and effect) which sets out measures to encourage sustainable means of transport (public, cycling and walking) via subsidised or free-ticketing, improved links to bus stops, improved infrastructure and layouts to improve accessibility and safety;
- All gas-fired boilers to meet a minimum standard of <40 mgNO_x/kWh;
- Where emissions are likely to impact on an AQMA, all gas-fired CHP plant to meet a minimum emissions standard of:
 - Spark ignition engine: 250 mgNO_x/Nm³;
 - Compression ignition engine: 400 mgNO_x/Nm³;
 - Gas turbine: 50 mgNO_x/Nm³.
- A presumption should be to use natural gas-fired installations. Where biomass is proposed within an urban area it is to meet minimum emissions standards of 275 mgNO_x/Nm³ and 25 mgPM/Nm³.

A2.5 The guidance also outlines that offsetting emissions might be used as a mitigation measure for a proposed development. However, it states that:

“It is important that obligations to include offsetting are proportional to the nature and scale of development proposed and the level of concern about air quality; such offsetting can be based on a quantification of the emissions associated with the development. These emissions can be assigned a value, based on the “damage cost approach” used by Defra, and then applied as an indicator of the level of offsetting required, or as a financial obligation on the developer. Unless some form of benchmarking is applied, it is impractical to include building emissions in this approach, but if the boiler and CHP emissions are consistent with the standards as described above then this is not essential”.

A2.6 The guidance offers a widely used approach for quantifying costs associated with pollutant emissions from transport. It also outlines the following typical measures that may be considered to offset emissions, stating that measures to offset emissions may also be applied as post assessment mitigation:

- Support and promotion of car clubs;
- Contributions to low emission vehicle refuelling infrastructure;
- Provision of incentives for the uptake of low emission vehicles;
- Financial support to low emission public transport options; and
- Improvements to cycling and walking infrastructures.

Screening

Impacts of the Local Area on the Development

“There may be a requirement to carry out an air quality assessment for the impacts of the local area’s emissions on the proposed development itself, to assess the exposure that residents or users might experience. This will need to be a matter of judgement and should take into account:

- the background and future baseline air quality and whether this will be likely to approach or exceed the values set by air quality objectives;*
- the presence and location of Air Quality Management Areas as an indicator of local hotspots where the air quality objectives may be exceeded;*
- the presence of a heavily trafficked road, with emissions that could give rise to sufficiently high concentrations of pollutants (in particular nitrogen dioxide), that would cause unacceptably high exposure for users of the new development; and*
- the presence of a source of odour and/or dust that may affect amenity for future occupants of the development”.*

Impacts of the Development on the Local Area

A2.7 The guidance sets out two stages of screening criteria that can be used to identify whether a detailed air quality assessment is required, in terms of the impact of the development on the local area. The first stage is that you should proceed to the second stage if any of the following apply:

- 10 or more residential units or a site area of more than 0.5 ha residential use; and/or
- more than 1,000 m² of floor space for all other uses or a site area greater than 1 ha.

A2.8 Coupled with any of the following:

- the development has more than 10 parking spaces; and/or
- the development will have a centralised energy facility or other centralised combustion process.

A2.9 If the above do not apply then the development can be screened out as not requiring a detailed air quality assessment of the impact of the development on the local area. If they do apply then you proceed to stage 2, which sets out indicative criteria for requiring an air quality assessment. The stage 2 criteria relating to vehicle emissions are set out below:

- the development will lead to a change in LDV flows of more than 100 AADT within or adjacent to an AQMA or more than 500 AADT elsewhere;
- the development will lead to a change in HDV flows of more than 25 AADT within or adjacent to an AQMA or more than 100 AADT elsewhere;
- the development will lead to a realigning of roads (i.e. changing the proximity of receptors to traffic lanes) where the change is 5m or more and the road is within an AQMA;
- the development will introduce a new junction or remove an existing junction near to relevant receptors, and the junction will cause traffic to significantly change vehicle acceleration/deceleration, e.g. traffic lights or roundabouts;
- the development will introduce or change a bus station where bus flows will change by more than 25 AADT within or adjacent to an AQMA or more than 100 AADT elsewhere; and
- the development will have an underground car park with more than 100 movements per day (total in and out) with an extraction system that exhausts within 20 m of a relevant receptor.

A2.10 The criteria are more stringent where the traffic impacts may arise on roads where concentrations are close to the objective. The presence of an AQMA is taken to indicate the possibility of being close to the objective, but where whole authority AQMAs are present and it is known that the affected roads have concentrations below 90% of the objective, the less stringent criteria are likely to be more appropriate.

A2.11 On combustion processes (including standby emergency generators and shipping) where there is a risk of impacts at relevant receptors, the guidance states that:

“Typically, any combustion plant where the single or combined NO_x emission rate is less than 5 mg/sec is unlikely to give rise to impacts, provided that the emissions are released from a vent or stack in a location and at a height that provides adequate dispersion. As a guide, the 5 mg/s criterion equates to a 450 kW ultra-low NO_x gas boiler or a 30kW CHP unit operating at <95mg/Nm³.

In situations where the emissions are released close to buildings with relevant receptors, or where the dispersion of the plume may be adversely affected by the size and/or height of adjacent buildings (including situations where the stack height is lower than the receptor) then consideration will need to be given to potential impacts at much lower emission rates.

Conversely, where existing nitrogen dioxide concentrations are low, and where the dispersion conditions are favourable, a much higher emission rate may be acceptable”.

- A2.12 Should none of the above apply then the development can be screened out as not requiring a detailed air quality assessment of the impact of the development on the local area, provided that professional judgement is applied; the guidance importantly states the following:

“The criteria provided are precautionary and should be treated as indicative. They are intended to function as a sensitive ‘trigger’ for initiating an assessment in cases where there is a possibility of significant effects arising on local air quality. This possibility will, self-evidently, not be realised in many cases. The criteria should not be applied rigidly; in some instances, it may be appropriate to amend them on the basis of professional judgement, bearing in mind that the objective is to identify situations where there is a possibility of a significant effect on local air quality”.

- A2.13 Even if a development cannot be screened out, the guidance is clear that a detailed assessment is not necessarily required:

“The use of a Simple Assessment may be appropriate, where it will clearly suffice for the purposes of reaching a conclusion on the significance of effects on local air quality. The principle underlying this guidance is that any assessment should provide enough evidence that will lead to a sound conclusion on the presence, or otherwise, of a significant effect on local air quality. A Simple Assessment will be appropriate, if it can provide this evidence. Similarly, it may be possible to conduct a quantitative assessment that does not require the use of a dispersion model run on a computer”.

- A2.14 The guidance also outlines what the content of the air quality assessment should include, and this has been adhered to in the production of this report.

Assessment of Significance

- A2.15 There is no official guidance in the UK in relation to development control on how to describe the nature of air quality impacts, nor how to assess their significance. The approach within the EPUK/IAQM guidance has, therefore, been used in this assessment. This approach involves a two stage process:

- a qualitative or quantitative description of the impacts on local air quality arising from the development; and
- a judgement on the overall significance of the effects of any impacts.

- A2.16 The guidance recommends that the assessment of significance should be based on professional judgement, with the overall air quality impact of the development described as either ‘significant’ or ‘not significant’. In drawing this conclusion, the following factors should be taken into account:

- the existing and future air quality in the absence of the development;
- the extent of current and future population exposure to the impacts;
- the influence and validity of any assumptions adopted when undertaking the prediction of impacts;
- the potential for cumulative impacts and, in such circumstances, several impacts that are described as '*slight*' individually could, taken together, be regarded as having a significant effect for the purposes of air quality management in an area, especially where it is proving difficult to reduce concentrations of a pollutant. Conversely, a '*moderate*' or '*substantial*' impact may not have a significant effect if it is confined to a very small area and where it is not obviously the cause of harm to human health; and
- the judgement on significance relates to the consequences of the impacts; will they have an effect on human health that could be considered as significant? In the majority of cases, the impacts from an individual development will be insufficiently large to result in measurable changes in health outcomes that could be regarded as significant by health care professionals.

A2.17 The guidance is clear that other factors may be relevant in individual cases. It also states that the effect on the residents of any new development where the air quality is such that an air quality objective is not met will be judged as significant. For people working at new developments in this situation, the same will not be true as occupational exposure standards are different, although any assessment may wish to draw attention to the undesirability of the exposure.

A2.18 A judgement of the significance should be made by a competent professional who is suitably qualified. A summary of the professional experience of the staff contributing to this assessment is provided in Appendix A3.

A3 Professional Experience

Dr Denise Evans, BSc (Hons) PhD MEnvSc MIAQM

Dr Evans is an Associate Director with AQC, with more than 24 years' relevant experience. She has prepared air quality review and assessment reports for local authorities, and has appraised local authority air quality assessments on behalf of the UK governments, and provided support to the Review and Assessment helpdesk. She has extensive modelling experience, completing air quality and odour assessments to support applications for a variety of development sectors including residential, mixed use, urban regeneration, energy, commercial, industrial, and road schemes, assessing the effects of a range of pollutants against relevant standards for human and ecological receptors. Denise has acted as an Expert Witness and is a Member of the Institute of Air Quality Management.

Julia Burnell, MEnvSci (Hons) MEnvSc MIAQM

Miss Burnell is a Senior Consultant with AQC with over seven years' experience in the field of air quality. She has experience of undertaking a range of air quality assessments for power, transportation, and mixed-use development projects both in the UK and internationally. She is also experienced at preparing environmental permit applications for medium combustion plant/specified generator sites and has commissioned and maintained numerous ambient air quality monitoring surveys. Prior to her work with AQC, Julia completed an MEnvSci (Hons) in Environmental Science (four-year integrated master's). She is a Member of both the Institute of Air Quality Management and the Institution of Environmental Sciences.

Ben Collier, BSc (Hons)

Mr Collier is an Assistant Consultant with AQC and joined the company in 2023. Throughout his BSc Environmental Science degree at the University of the West of England, he developed an interest in planetary processes and impacts, in particular those in relation to air quality. During his studies, Mr Collier completed several atmospheric-related projects, with topics varying from the impact of urban air pollution to the potential of renewable energy to improve air quality; many of these included GIS based analysis.

A4 Construction Mitigation

A4.1 Table A4.1 sets out a list of best-practice measures from the IAQM guidance (IAQM, 2016) that should be incorporated into the specification for the works. These measures should ideally be written into a Dust Management Plan. Some of the measures may only be necessary during specific phases of work, or during activities with a high potential to produce dust, and the list should be refined and expanded upon in liaison with the construction contractor when producing the Dust Management Plan.

Table A4.1: Best-Practice Mitigation Measures Recommended for the Works

Measure	Desirable	Highly Recommended
Communications		
Display the name and contact details of person(s) accountable for air quality and dust issues on the site boundary. This may be the environmental manager/engineer or the site manager		✓
Display the head or regional office contact information		✓
Dust Management Plan		
Develop and implement a Dust Management Plan (DMP) approved by the Local Authority which documents the mitigation measures to be applied, and the procedures for their implementation and management	✓	
Site Management		
Record all dust and air quality complaints, identify cause(s), take appropriate measures to reduce emissions in a timely manner, and record the measures taken		✓
Make the complaints log available to the local authority when asked		✓
Record any exceptional incidents that cause dust and/or air emissions, either on- or off- site, and the action taken to resolve the situation in the log book		✓
Monitoring		
Undertake daily on-site and off-site inspections where receptors (including roads) are nearby, to monitor dust. Record inspection results, and make the log available to the Local Authority when asked. This should include regular dust soiling checks of surfaces such as street furniture, cars and window sills within 100 m of the site boundary, with cleaning to be provided if necessary	✓	
Carry out regular site inspections to monitor compliance with the DMP, record inspection results, and make an inspection log available to the Local Authority when asked		✓
Increase the frequency of site inspections by the person accountable for air quality and dust issues on site when activities with a high potential to produce dust are being carried out and during prolonged dry or windy conditions		✓
Preparing and Maintaining the Site		
Plan the site layout so that machinery and dust-causing activities are located away from receptors, as far as is possible		✓

Erect solid screens or barriers around dusty activities or the site boundary that are at least as high as any stockpiles on site		✓
Fully enclose site or specific operations where there is a high potential for dust production and the site is active for an extensive period	✓	
Avoid site runoff of water or mud		✓
Keep site fencing, barriers and scaffolding clean using wet methods	✓	
Remove materials that have a potential to produce dust from site as soon as possible, unless being re-used on site. If they are being re-used on-site cover as described below	✓	
Cover, seed, or fence stockpiles to prevent wind whipping	✓	
Operating Vehicle/Machinery and Sustainable Travel		
Ensure all vehicles switch off their engines when stationary – no idling vehicles		✓
Avoid the use of diesel- or petrol-powered generators and use mains electricity or battery-powered equipment where practicable		✓
Operations		
Only use cutting, grinding or sawing equipment fitted or in conjunction with suitable dust suppression techniques such as water sprays or local extraction, e.g. suitable local exhaust ventilation systems		✓
Ensure an adequate water supply on the site for effective dust/particulate matter suppression/mitigation, using non-potable water where possible and appropriate		✓
Use enclosed chutes, conveyors and covered skips		✓
Minimise drop heights from conveyors, loading shovels, hoppers and other loading or handling equipment and use fine water sprays on such equipment wherever appropriate		✓
Ensure equipment is readily available on site to clean any dry spillages, and clean up spillages as soon as reasonably practicable after the event using wet cleaning methods	✓	
Waste Management		
Avoid bonfires and burning of waste materials		✓
Measures Specific to Demolition		
Soft strip inside buildings before demolition (retaining walls and windows in the rest of the building where possible, to provide a screen against dust)	✓	
Ensure effective water suppression is used during demolition operations. Hand held sprays are more effective than hoses attached to equipment as the water can be directed to where it is needed. In addition high volume water suppression systems, manually controlled, can produce fine water droplets that effectively bring the dust particles to the ground		✓
Avoid explosive blasting, using appropriate manual or mechanical alternatives		✓
Bag and remove any biological debris or damp down such material before demolition		✓
Measures Specific to Construction		
Avoid scabbling (roughening of concrete surfaces), if possible	✓	

Ensure sand and other aggregates are stored in bunded areas and are not allowed to dry out, unless this is required for a particular process, in which case ensure that appropriate additional control measures are in place	✓	
Measures Specific to Trackout		
Use water-assisted dust sweeper(s) on the access and local roads, to remove, as necessary, any material tracked out of the site. This may require the sweeper being continuously in use	✓	
Avoid dry sweeping of large areas	✓	
Ensure vehicles entering and leaving sites are covered to prevent escape of materials during transport	✓	
Record all inspections of haul routes and any subsequent action in a site log book;	✓	